

Optische Kabel mit Stahlarmierung

Optical cable steel armoured

- ✓ Single mode Kabel
- ✓ 3 mm Durchmesser
- ✓ Dämpfung 0,3 dB/km
- ✓ Biegeradius > 10 mm
- ✓ FC/PC Stecker
- ✓ UV-beständig
- ✓ Farbe grau
- ✓ OAK 010-01...OAK 030-01 im Ring
- ✓ OAK 050-01...OAK 200-01 auf Holztrommel
- ✓ Single mode cable
- ✓ 3 mm diameter
- ✓ Attenuation 0,3 dB/km
- ✓ Bending radius > 10 mm
- ✓ FC/PC male
- ✓ UV stabilised
- ✓ Colour gray
- ✓ OAK 010-01...OAK 030-01 in a ring
- ✓ OAK 050-01...OAK 200-01 on a wooden drum

premium-line



Type Type	Bestellnummer Part No.	Länge Length	Type Type	Bestellnummer Part No.	Länge Length
OAK 10-01	OAK01001	10,00 m	OAK 50-01	OAK05001	50,00 m
OAK 20-01	OAK02001	20,00 m	OAK 100-01	OAK10001	100,00 m
OAK 30-01	OAK03001	30,00 m	OAK 200-01	OAK20001	200,00 m

Optische Kabel

Optical cable

- ✓ Single mode Kabel
- ✓ 3 mm Durchmesser
- ✓ Dämpfung 0,3 dB/km
- ✓ Biegeradius > 10 mm
- ✓ FC/PC-Stecker
- ✓ UV-beständig
- ✓ Farbe weiß
- ✓ OAK 001-02...OAK 050-02 im Polybeutel
- ✓ OAK 100-02...OAK 200-02 auf Kunststofftrommel
- ✓ OAK 500-02 auf Holztrommel
- ✓ Single mode cable
- ✓ 3 mm diameter
- ✓ Attenuation 0,3 dB/km
- ✓ Bending radius > 10 mm
- ✓ FC/PC male
- ✓ UV stabilised
- ✓ Colour white
- ✓ OAK 001-02...OAK 030-02 in a polybag
- ✓ OAK 100-02...OAK 200-02 on a plastic drum
- ✓ OAK 500-02 on a wooden drum

premium-line



Type Type	Bestellnummer Part No.	Länge Length	Type Type	Bestellnummer Part No.	Länge Length
OAK 1-02	OAK00102	1,00 m	OAK 30-02	OAK03002	30,00 m
OAK 5-02	OAK00502	5,00 m	OAK 50-02	OAK05002	50,00 m
OAK 10-02	OAK01002	10,00 m	OAK 100-02	OAK10002	100,00 m
OAK 20-02	OAK02002	20,00 m	OAK 200-02	OAK20002	200,00 m
			OAK 500-02	OAK50002	500,00 m