

760060905 | CAT 3 50 Port Panel



Category 3 U/UTP High Density Voice Patch Panel, 50 port

OBSOLETE

This product was discontinued on: December 1, 2016

Replaced By:

1711214-2	Telephone Patch Panel, category 3, RJ45, 19 in, 50-port, black
1711214-3	Telephone Patch Panel, category 3, RJ45, 19 in, 50-port, gray

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	SYSTIMAX®
Product Type	RJ45 patch panel
Ordering Note	Available in Europe, the Middle East and Africa

General Specifications

ANSI/TIA Category	3
Cable Type	Unshielded
Color	Black
Intelligence Type	Passive
Rack Type	EIA 19 in
Rack Units	1
Termination Type	IDC
Total Ports, quantity	50

Dimensions

Height	44.45 mm 1.75 in
Width	482.6 mm 19 in
Depth	139.7 mm 5.5 in

Electrical Specifications

Current Rating at Temperature	1.5 A @ 20 °C 1.5 A @ 68 °F
Dielectric Withstand Voltage, RMS, conductive surface	1,500 Vac @ 60 Hz

760060905 | CAT 3 50 Port Panel

Dielectric Withstand Voltage, RMS, contact-to-contact 1,000 Vac @ 60 Hz

Material Specifications

Termination Contact Plating Nickel

Environmental Specifications

Operating Temperature -10 °C to +60 °C (+14 °F to +140 °F)

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system

