

Copper Patch Panel

1 U 48 ports punch down Category 6A

Description

- 48 termination blocks in 1 U
- Increased cabinet utilisation
- Uniform cable termination-added flexibility of cable entry
- Built in rear cable management integral grounding clamp
- Robust steel construction



Technical data

Construction

Description	Values	Comment
Dimension (W x H x D)	482.6 x 43.65 x 123mm	
Colour	Silver	
Main construction	Metal	

Mechanical and environmental data

Characteristics	Values	Tested acc. to	Comment
For solid copper wire	AWG 22 ~AWG 24		
For strand copper wire	AWG 26/7 strand		
Insertion/extraction life	750 cycles minimum		
Compliant with RoHS and REACH	Yes		

Electrical data

Characteristics	Values	Tested acc. to	Comment
Insulation resistance	500 MΩ min. @100V d.c		
Dielectric withstanding voltage:	1000V d.c. or a.c. peak contact to contact @60Hz for 1 minute.		

Ordering information

Description	Item number	Comment
Category 6A punch down panel shielded, 1 U 48 ports, incl. earthing kit and cable management bar, silver	85066058	

Related documents

Description	Document number
User manual for installation	DOC-0000716398

Additional information

Description	
Microsite for Data Center solution	datacenter.hubersuhner.com