

MSE-M-48-K48-KLP

Fiber optic enclosures allows you to protect fibers and welds against mechanical damage and environmental influences, as well as simple fiber management.



Fiber optic splice closure

features:

- wall or pole mountine,
- mechanical locking system providing multiple access,
- cable ports: 3 round and 1 oval,
- optional cable port seals: heat shrink tubing for more cables,
- possibility of placing up to 48 welds,
- compact dimensions.

optional accessories and products:

- additional SK-MSE-M-12 splice cassettes
- MCE heat shrink sleeves,
- multiplier MI-MGM head with the Mi-MGM-RCE mounting set,
- heat-shrinkable weld seams.

included accessories:

- splice cassette - the number depends on the configuration,
- pre-installed wall mounting bracket,
- post mount bracket,
- 3 seals of round ports and 1 oval port,
- buckle for oval sealing,
- self-adhesive aluminum foil,
- zippers,
- self-adhesive tube markers,
- m8 screw wrench,
- earthing conductor.

sectors:



MSE-M-48-K48-KLP

technical specifications:

| MSE-M-48-K48-KLP | |
|-----------------------------------|-------------|
| dimensions [width x height] [mm] | 288 x 178 |
| max. number of cassettes | 4 |
| max. number of welds | 48 |
| number of round ports | 3 |
| the number of oval ports | 1 |
| max. number of cables inserted: * | |
| for 3 - 8 mm cables | 12 |
| for 5 - 9 mm cables | 9 |
| weight [kg] | 1,85 |
| IP protection | IP 68 |
| material | ABS plastic |

ordering:

| 0 | 1 | description |
|----------|-----|---|
| MSE-M-48 | | fiber optic closures |
| | K12 | fiber optic closures MSE-M-48, with single 12 splice tray |
| | K24 | fiber optic closures MSE-M-48, with two 12 splice trays |
| | K36 | fiber optic closures MSE-M-48, with three 12 splice trays |
| | K48 | fiber optic closures MSE-M-48, with four 12 splice trays |