


P/N: PD-SAC-108-F-15-F-30-0-AL

REVISIONS			
REV.	DESCRIPTION	DATE	REVISED
1.0	DRAWING ISSUED	7/24/2014	C.Li

Test data requirements:

Optical performance measurements are

- unidirectional
- taken at two wavelength: 1310 and 1550nm
- test report include IL, RL and PDL



Parameters	1x8
Operating Wavelength range (nm)	1260~1650
Insertion Loss Max. (dB)	10.5
Uniformity Max. (dB)	0.8
PDL Max.(dB)	0.3
Return Loss Min. (dB)	55
Directivity Min. (dB)	55
Operating Temperature (°C)	-40~+85
Storage Temperature (°C)	-40~+85
Fiber type	G.652D
Dimensions LxWxH (mm)	40x4x4

- Values taken at room temperature, 1310 and 1550nm, including PDL, but not including WDL and TDL.

CONFIDENTIAL

Category

Information on this document is proprietary and may not be used, copied, reproduced, or disclosed without the written consent of SENKO Advanced Components, Inc.

M

UNLESS OTHERWISE SPECIFIED:
DEBURRS ALL SHARP EDGES.
DIMENSIONS ARE AFTER FINISH

TOLERANCES:

X.: ±
.X.: ±
.XX.: ±
.XXX.: ±
∠.: ±

Item No.	Part Number	Description			Qty.
Drawn By Chris Li	Checked By	Approved by Frodo Liao	All Dimensions in mm Material:	Date 7/24/2014	Scale Free
 SENKO SENKO GROUP® Advanced Components		Name: 1x8 Bare Fiber PLC Splitter			
		Dwg.No: ENC-0714-941	Rev. 1.0	Sheet 1	