

Copper Jack

Cat 6a shielded

Description

For the transmission of digital and analogue voice, video and data signals. Suitable for all Category 6a or Class EA requirements in accordance with ISO/IEC 11801, EN 50173-1 and TIA/EIA 568-C.2. "

- Housing made of Zinc-alloy, fully shielded.
- With wiring colour code T568 A and B
- Suitable for POE+ application(GHMT approved)
- Keystone mounting clip
- Fast installation with press tool



Technical data

Construction

Description	Values	Comment
Dimension (W x D x H)	14.4 x 34.4 x 20.8 mm	
Main construction	Metal	
Suitable connector	RJ45	

Mechanical and environmental data

Characteristics	Values	Tested acc. to	Comment
For solid copper wire	AWG 22 ~AWG 24		
Insertion/extraction life	750 cycles minimum		
Compliant with RoHS and REACH	Yes		


Electrical data

Characteristics	Values	Tested acc. to	Comment
Insulation resistance	500 M Ω min.		
Dielectric withstanding voltage	1000V d.c. contact to contact		

Copper Jack

Cat 6a shielded

Technical drawing



Ordering information

Description	Item number	Comment
Category 6A jack , shielded, silver	85089757	

Related documents

Description	Document number
None	

Additional information

Description	
Microsite for Data Center solution	datacenter.hubersuhner.com