

GigaLine[®] patch cord

4 LC duplex - 1 MTP female

E9/125 OS2





Illustration similar

Description

Patch Cord industrial pre-assembled with divider head
 4x LC-Duplex- to 1x MTP®/female-plug.
 Length of the single elements: 0.5m.

Construction

Cable type	KL-I-F(ZN)H G50/125/OM4 - Cca
Colour of sheath	Heather violet
Connectors	LC/PC duplex - MPO/APC female
Diameter outer sheath	

Mechanical characteristics (cable)

Tensile strength	300 N
------------------	-------

Optical characteristics (connector A / connector B)

Polish	PC / APC
Insertion loss (max.)	0,3 dB / 0,3 dB
Insertion loss (typ.)	0,15 dB / 0,1 dB
Return loss (min.)	50 dB / 60 dB

Thermal characteristics (cable)

Temperature (transport / storage)	-25 °C up to +70 °C
Temperature during installation	-5 °C up to +50 °C
Temperature after installation	-10 °C up to +70 °C

Fire characteristics (cable)

Flame retardance	IEC 60332-1-2, IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1
Smoke density	IEC 61034
Brandklasse	Cca s1a d1 a2 acc. to EN 50575 / 50399

Standards, certificates and approvals

Fibre standard	OS2 ITU-T 652.D + G657.A1 IEC 60793-2 B1.3
Connector standard	IEC 61754-20 (LC), IEC 61754-7-1 / EIA/TIA 604-5 (MPO)
Cabling standard	EN 50173, ISO/IEC 11801
Chemical continuance	Free of hazardous substances acc. to RoHS 2011/65/EU

GigaLine[®] patch cord

4 LC duplex - 1 MTP female

E9/125 OS2

Cable length (m)	Wiring	Number of assembled fibers	Part number	Weight
2,0	SFF (KBG00011)	8	LKD9SPW2BA20020	0,066