drop passives gold series splitters



gold series - splitters

features and benefits

True performance

- Guaranteed minimum specifications

 GHz bandwidth
 Flat frequency response
 High return loss
 -110 dB shield effectiveness (RFI)
 Printed circuit board construction

 Convenience and installation ease

- ✓ Individually plastic packaged with screws
 ✓ Machine threaded ports
 ✓ Solder back housings

Protection and prevention

✓ Zinc alloy die-cast housing, tin plated



parameter	value			
Nominal impedance	75 Ohms			
Insertion loss flatness	± 0.5 dB			

ordering information

ordering information

part number	description
PCT-1000-2W	Splitter, gold series, 1 GHz, 2-way, solder back
PCT-1000-3W	Splitter, gold series, 1 GHz, 3-way, solder back
PCT-1000-3WB	Splitter, gold series, 1 GHz, 3-way bal, solder back
PCT-1000-4W	Splitter, gold series, 1 GHz, 4-way, solder back
PCT-1000-6W	Splitter, gold series, 1 GHz, 6-way, solder back
PCT-1000-8W	Splitter, gold series, 1 GHz, 8-way, solder back

specifications

MHz	PCT-1000-xW Tap Value (Typical / dB)							
	Insertion Loss							
5 - 47	3.5	3.5 / 6.9	5.8	6.9	9.3	10.3		
48 - 450	3.9	3.9 / 7.3	6.2	7.3	9.6	11.0		
451 - 750	3.9	3.9 / 7.5	6.5	7.5	9.9	11.5		
751 - 1002	4.0	4.0 / 8.0	7.0	8.0	11,0	12.5		
Isolation Loss								
5 - 47	20	25	25	25	25	25		
48 - 450	26	24	25	24	24	24		
451 - 750	22	23	24	23	22	22		
751 - 1002	22	21	22	21	21	21		
Return Loss (I	n/Out)							
5 - 47	20	18	18	18	18	18		
48 - 450	22	21	21	20	22	22		
451 - 750	20	21	21	20	20	20		
751 - 1002	18	18	18	18	18	18		













