

**This specification is OBSOLETE**



K Closure, 6.5 in OD, three drop ports, one 24-fiber tray

**OBSOLETE**

## Product Classification

<b>Product Type</b>	Single-ended, round fiber closure
<b>Regional Availability</b>	North America
<b>Product Series</b>	OFE

## General Specifications

<b>Splicing Capacity, Single Fusion, maximum</b>	288
<b>Application</b>	For loose tube, central tube, micro-sheath/duct and blown fiber cable
<b>Color</b>	Black
<b>Includes</b>	Mounting hardware   Splice tray (1)
<b>Package, quantity</b>	1
<b>Splice Tray Supported, quantity</b>	6
<b>Splicing Capacity, Single Splice, 12 fibers, maximum</b>	288

## Dimensions

<b>Cable Entry Drop Port Diameter</b>	25 mm
<b>Cable Entry Main Port Diameter</b>	25 mm
<b>Diameter</b>	165.10 mm   6.50 in
<b>Length</b>	622.30 mm   24.50 in
<b>Weight</b>	6.17 kg   13.60 lb

## Mechanical Specifications

<b>Cable Ports, quantity</b>	4
<b>Closure Style</b>	Single-ended
<b>Material Type</b>	Molded plastic

## Environmental Specifications

<b>Environmental Space</b>	Above ground   Below ground
----------------------------	-----------------------------

**Operating Temperature**

-40 °C to +70 °C (-40 °F to +158 °F)

**Qualification Standard**

Telcordia GR-20-CORE

## Included Products

9703146/00 | OFE-CLS-K-MNT-POL/AIR — Mounting Hardware for K Closure for Pole and Aerial Mounting

9703149/00 | OFE-CLS-K/L-SPT-24 — Splice tray for K and L Closures for 24 Single Fusion Splices