

Data sheet


OpDAT PF patch panel VIK
6xLC-D (blue), OS2, gray

Page 1/5


P/N
1502007406-E
EAN 4250184188162

2018-27-02

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel for fixed installation
- equipped with LC-D adapters
- prepared for fixation of pre-terminated installation cables (OpDAT VIK)
- light construction with aluminum front plate (gray or black) and housing
- unequipped cutouts are closed with blind plugs
- removable front plate for easy adapter mounting
- 10 possible cable entries in the rear panel for 4x PG13.5, 2x PG16/M20 or 2x PG21/M25 cable glands and for two pre-terminated installation cables (VIK)
- snap-on cover for easy access during service work
- label windows for enclosed identification labels
- variants: equipped with 6, 12 or 24 LC-D adapters each blue (OS2), lime green (OM5), heather violet (OM4), aqua (OM3) or 6, 12 or 24 LC-D APC adapters green (OS2)



Data sheet

OpDAT PF patch panel VIK 6xLC-D (blue), OS2, gray

Page 2/5

P/N

1502007406-E

EAN 4250184188162

2018-27-02

Technical Data

General Data

Fields of application

	Office
	Data center
Design	patch panel
Mounting style	1RU
Transmission technology	Fiber optic
Port numbering	yes
Color	blue
Dimensions	
Dimension (L x W x H)	258.00 x 482.60 x 44.45 mm
Dimension (L x W x H)	10.157 x 19.00 x 1.75 in.
Inches	19 inches
Height unit	1RU
Mode type of the fiber	Single mode
Labeling option	label window with identification label + printed numbers

Connections/interfaces

Connector technology interface 1	LC-D Couplers
Connector technology interface 2	LC-D Couplers
Number of ports interface 1	24
Number of ports interface 2	24
Number of equipped ports interface 1	6
Number of ports interface 2 equipped	6
Number of ports with dust protection interface 1	6
Number of ports with dust protection interface 2	6
Number of blind covers interface 2	18
Cable access/outlet	several possibilities for cable entry on the back

Mechanical characteristics

Cut-out	SC, LC-D, E2000
Connector type	Duplex
Life - Number of mating cycles	min. 1000
strain relief	yes



Data sheet

OpDAT PF patch panel VIK 6xLC-D (blue), OS2, gray

Page 3/5

P/N

1502007406-E

EAN 4250184188162

2018-27-02

Technical Data

Materials and material properties

Material - Housing	Al (Aluminium)
Material - Front cover	Al (Aluminium)
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics

Approvals

RoHS	compliant
------	-----------

The product meets the following standards

Fibre optic connector interfaces	DIN EN 61754-20
----------------------------------	-----------------

Packing details

Type of packaging	1 pc(s) / box
Packaging dimension (W x H x D)	540.00 x 380.00 x 60.00 mm
Packaging dimension (W x H x D)	21.26 x 14.961 x 2.362 in.



Data sheet

**OpDAT PF patch panel VIK
6xLC-D (blue), OS2, gray**

Page 4/5

P/N

1502007406-E

EAN 4250184188162

2018-27-02

Accessories

P/N	Designation
899789-01	Label sheet for E-DAT C6 and E-DAT design patch panels



P | Cabling

Data sheet

OpDAT PF patch panel VIK 6xLC-D (blue), OS2, gray

Page 5/5

P/N

1502007406-E

EAN 4250184188162

2018-27-02

Illustrations

Dimensional drawing

