

Data sheet

OpDAT PF patch panel VIK
12xLC-D (violet), OM4, gray

Page 1/5


P/N
1502007512-E
EAN 4250184188230

2018-13-03

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel for fixed installation
- equipped with LC-D adapters
- prepared for fixation of pre-terminated installation cables (OpDAT VIK)
- light construction with aluminum front plate (gray or black) and housing
- unequipped cutouts are closed with blind plugs
- removable front plate for easy adapter mounting
- 10 possible cable entries in the rear panel for 4x PG13.5, 2x PG16/M20 or 2x PG21/M25 cable glands and for two pre-terminated installation cables (VIK)
- snap-on cover for easy access during service work
- label windows for enclosed identification labels
- variants: equipped with 6, 12 or 24 LC-D adapters each blue (OS2), lime green (OM5), heather violet (OM4), aqua (OM3) or 6, 12 or 24 LC-D APC adapters green (OS2)



P | Cabling

Data sheet

OpDAT PF patch panel VIK 12xLC-D (violet), OM4, gray

Page 2/5

P/N

1502007512-E

EAN 4250184188230

2018-13-03

Technical Data

General Data

Fields of application

Structured building cabling, Office
Data center

Design patch panel

Mounting style 1RU

Transmission technology Fiber optic

Port numbering yes

Color violet

Dimensions

Dimension (L x W x H) 258.00 x 482.60 x 44.45 mm

Dimension (L x W x H) 10.157 x 19.00 x 1.75 in.

Inches 19 inches

Height unit 1RU

Mode type of the fiber Multimode

Fiber construction 50/125 µm

Labeling option label window with identification label + printed numbers

Connections/interfaces

Connector technology interface 1 LC-D Couplers

Connector technology interface 2 LC-D Couplers

Number of ports interface 1 24

Number of ports interface 2 24

Number of equipped ports interface 1 12

Number of equipped ports interface 2 12

Number of ports with dust protection interface 1 12

Number of ports with dust protection interface 2 12

Number of blind covers interface 2 12

Cable access/outlet several possibilities for cable entry on the back

Mechanical characteristics

Life - Number of mating cycles min. 1000

strain relief yes



Data sheet

Page 3/5

OpDAT PF patch panel VIK 12xLC-D (violet), OM4, gray

P/N

1502007512-E

EAN 4250184188230

2018-13-03

Technical Data

Materials and material properties

Material - Housing	Al (Aluminium)
Material - Front cover	Al (Aluminium)
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics

Approvals

RoHS	compliant
------	-----------

The product meets the following standards

Fibre optic connector interfaces	DIN EN 61754-20
----------------------------------	-----------------

Packing details

Type of packaging	1 pc(s) / box
Packaging dimension (W x H x D)	540.00 x 380.00 x 60.00 mm
Packaging dimension (W x H x D)	21.26 x 14.961 x 2.362 in.



Data sheet

Page 4/5

**OpDAT PF patch panel VIK
12xLC-D (violet), OM4, gray**

**P/N
1502007512-E
EAN 4250184188230**

2018-13-03

Accessories

P/N	Designation
899789-01	Label sheet for E-DAT C6 and E-DAT design patch panels



P | Cabling

Data sheet

OpDAT PF patch panel VIK 12xLC-D (violet), OM4, gray

Page 5/5

P/N

1502007512-E

EAN 4250184188230

2018-13-03

Illustrations

Dimensional drawing

