

Data sheet

OpDAT PA patch panel splice 6xSC-D (violet), OM4, gray

Page 1/6

P/N

150227BB06-E


EAN 4250184168782

2018-13-03

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel with pull-out splice tray / front cover (gray or black)
- equipped with SC-D adapters and SC pigtails
- pigtails with semi-tight buffered fiber dia. 0.9 mm, 12 colors, secondary and primary coating in the same color, length 2.0 m
- pigtails inserted and stripped in standard splice trays with crimp splice holders
- pigtails are cleaned and plugged in adapters
- splice tray can be tilted and completely removed to facilitate fitting (end stop)
- light aluminum construction
- unused cutouts are closed by blank plugs
- variable cable entry (straight / inclined) from both sides possible
- cable arrest with supplied cable tie or optional cable screw connection also possible.
- cable diameter from 3 to 20 mm
- strain relief for central element / Kevlar
- cable management by cable guides to be positioned as required
- screwless cover
- label windows for enclosed identification labels
- variants: equipped with 6, 12 or 24 SC-D adapters and pigtails, all blue (OS2), lime green (OM5), violet (OM4), aqua (OM3) or 6, 12 or 24 SC-D APC adapters and pigtails green (OS2)



Data sheet

OpDAT PA patch panel splice 6xSC-D (violet), OM4, gray

Page 2/6

P/N

150227BB06-E

EAN 4250184168782

2018-13-03

Technical Data

General Data

Fields of application

	Structured building cabling, Office Data center
Design	patch panel
Mounting style	1RU
Transmission technology	Fiber optic
Port numbering	yes
Color	violet
Dimensions	
Dimension (L x W x H)	264.50 x 482.60 x 44.45 mm
Dimension (L x W x H)	10.413 x 19.00 x 1.75 in.
Inches	19 inches
Height unit	1RU
Installation depth	265.00 mm
Installation depth	10.433 in.
Number of cables/ cores	12
Cable Type	pigtail(s)
Fiber class	OM4: ISO/IEC 11801/EN 50173 & IEC 60793-2-10/EN 60793-2-10 A1.a.3
Mode type of the fiber	Multimode
Fiber construction	50/125 µm
Labeling option	label window with identification label + printed numbers

Connections/interfaces

Connector technology interface 1	SC-D Couplers
Connector technology interface 2	SC-D Couplers
Number of ports interface 1	12
Number of ports interface 2	12
Number of equipped ports interface 1	6
Number of equipped ports interface 2	6
Number of ports with dust protection interface 2	6
Number of blind covers interface 2	6
Semi-tight buffered fiber pigtail length	2.00 m
Semi-tight buffered fiber pigtail length	6.56 ft
Semi-tight buffered fiber pigtail diameter	0.90 mm
Semi-tight buffered fiber pigtail diameter	0.035 in.



Data sheet

OpDAT PA patch panel splice 6xSC-D (violet), OM4, gray

Page 3/6

P/N
150227BB06-E
EAN 4250184168782

2018-13-03

Technical Data

Connections/interfaces

Cable access/outlet	variable, straight / inclined, from both sides possible
---------------------	---

Optical characteristics

Insertion loss	max. 0.4 dB
Return loss	min. 35 dB

Mechanical characteristics

Cut-out	SC-D, LC-Q, ST-D
Connector type	Duplex
Life - Number of mating cycles	min. 1000
strain relief	yes

Materials and material properties

Material - Housing	Al (Aluminium)
Material - Front cover	Al (Aluminium)
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics

Approvals

RoHS	compliant
------	-----------

The product meets the following standards

Fibre optic connector interfaces	DIN EN 61754-4
Optical fibers: Product specifications	
Sectional specification for category A1 multimode fibres	ISO/IEC 60793-2-10 (A1a.3)
Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
Fibre optic interconnecting devices and passive components	IEC 61300-3-4
Fibre optic interconnecting devices and passive components	IEC 61300-3-6
Fibre optic interconnecting devices and passive components	IEC 61300-3-35
Standard colours for insulation for low-frequency cables & wires	IEC 60304



Data sheet

Page 4/6

OpDAT PA patch panel splice 6xSC-D (violet), OM4, gray

P/N

150227BB06-E

EAN 4250184168782

2018-13-03

Technical Data

Classifications

ETIM 5.0	EC001130
ETIM 6.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
Packaging unit - Weight (gram)	2380.00 g
Packaging unit - Weight (pound)	5.25 lb
Packaging dimension (W x H x D)	523.00 x 361.00 x 45.00 mm
Packaging dimension (W x H x D)	20.591 x 14.213 x 1.772 in.



Data sheet

OpDAT PA patch panel splice 6xSC-D (violet), OM4, gray

Page 5/6

P/N

150227BB06-E

EAN 4250184168782

2018-13-03

Accessories

P/N	Designation
899789-01	Label sheet for E-DAT C6 and E-DAT design patch panels



Data sheet

OpDAT PA patch panel splice 6xSC-D (violet), OM4, gray

Page 6/6

P/N

150227BB06-E

EAN 4250184168782

2018-13-03

Illustrations

Dimensional drawing

