

SKB 88-04 Coaxial cable | 2-way shielded



- ✓ For SAT or CATV indoor installation
- ✓ Fire behavior Eca acc. to EN 50575
- ✓ Inner conductor StCu, diameter 1.02 mm
- ✓ Physically-foamed dielectric, diameter 4.7 mm
- ✓ Screening aluminium foil/aluminium braiding
- ✓ Jacket PVC, white
- ✓ Degressive metering
- ✓ 250 m in a opti-box

Order information

Type	SKB 88-04
Order no.	SKB08804
GTIN	7611682118742
PE	1
VE	2
EU customs tariff number	85442000



Technical data

Electrical data

Impedance	75 Ω
Attenuation	8.4 dB / 100 m @ 200 MHz 17.8 dB / 100 m @ 800 MHz 32.1 dB / 100 m @ 2400 MHz
Screening factor	> 85 dB @ 30...1000 MHz > 80 dB @ 1000...2000 MHz > 80 dB @ 2000...3000 MHz
Coupling resistance	<16mOhm/m

Mechanical data

Inner conductor material diameter	StCu 1.02 mm
Dielectric diameter	4.7 mm
Braiding opt. coverage	64 x 0.12 mm 45%
Jacket material diameter	PVC 6.8 mm
Bending radius single multiple	24 mm 68 mm

General

Application temperature range	-5...+50°C
Operating temperature range	-20...+75°C
Fire behavior	Eca
Weight	9.675 kg

Suitable products

[TZU 20-01 Carrying strap](#)
[CKS 7-48 IEC | male | compression](#)
[CKK 7-48 IEC | female | compression](#)
[CFS 97-48 F | male | compression](#)
[CFS 99-48 F | male | compression | Quickfix](#)
[CFS 100-48 F | male | compression | Quickfix](#)
[CFS 93-48 F | Opti-fix | male | self compression](#)
[SZU 11-01 Water protection sleeve](#)