

SPU 82-00 DiSEqC switch | outdoor



- ✓ 2 × 4 in 1
- ✓ DC power pass
- ✓ Outdoor types in weather-proof housing (easy to mount with cable binders)

Order information

|                          |               |
|--------------------------|---------------|
| Type                     | SPU 82-00     |
| Order no.                | SPU08200      |
| GTIN                     | 7611682000290 |
| PE                       | 1             |
| VE                       | 1             |
| EU customs tariff number | 85291095      |



Technical data

|                                                |                   |
|------------------------------------------------|-------------------|
| Inputs                                         |                   |
| Number                                         | 2 × 4             |
| Frequency range                                | 950...2200 MHz    |
| Isolation SAT inputs   SAT inputs              | ≥ 30 dB           |
| Subscriber ports                               |                   |
| Number                                         | 2                 |
| Switch commands                                | Position   Option |
| Supported DiSEqC level                         | 1.0   2.0         |
| Tap loss SAT                                   | typ. 4 dB         |
| Connectors                                     |                   |
| Connector type                                 | F                 |
| General                                        |                   |
| Operating temperature range (acc. to EN 60065) | -20...+50°C       |
| Dimensions (W × H × D) appr.                   | 110 × 120 × 50 mm |
| Weight                                         | 0.258 kg          |

## Example of use

