
SEAS-NVE No. 59176 Duct Cable Data Sheet

Data Sneet DNL-100643-01

> Issue 3 May 2014



r AFL

EAN 5711760000463

Application

AFL Duct cables are designed with cable strength suitable for pulling into ducts and sub ducts. This design is also lightweight with a low friction jacket suitable for blowing installations.

Features and Benefits

- Fibre count 96
- 12 fibre management
- Dry water blocking
- Metal-free therefore not subject to EMI or earth-binding requirements
- Low friction outer sheath for easy handling and installation
- Lightweight and robust

Construction			OD (mm)	
1	1 Up-Jacketed Central Strength Member 4		4	
2	2 8 Gel Filled Loose Tubes, 12 fibres per tube		2.2	
3	Mylar Tape		8.40 (± 0.2)	
4	Outer Jacket and Ripcords		12.0 (± 0.2)	
Cable	Properties			
Weight		113	kg/km	
Diameter		12.0	mm	
Cross Section			113.1	mm ²
G652.D Fibre Attenuation at 1310nm			0.36	dB/km
G652.D Fibre Attenuation at 1550nm		0.22	dB/km	
Bend radius Static Dynamic		240	mm	
		1200		
Maximum Optical Working Tension (MOWT)		2.6	kN	
Cable Breaking Strength		7.3	kN	
Modulus		3.3	GPa	
Operating temperature range			-30 to 70	°C

Jacket Marking

"AFL Telecommunications - 96Fibre (SM 8 x 12) Optical Cable" - <Unique reel ID> <DD/MM/YYYY> <Metre Mark> "SEAS-NVE 59176 - Tel No 70 29 29 00"

Applicable Standards				
Fibre Standards:	ITU-T G.652.D			
Tube Colours: Fibre Colours:	G12FT, Y12FT, Y12FT, Y12FT, Y12FT, Y12FT, Y12FT, R12FT Red, Green, Blue, Yellow, White, Grey, Brown, Violet, Turquoise, Black, Orange, Pink			
Testing standards	IEC-60794-1-E1, EIA-455-33B			
Quality	Cable is designed, manufactured and tested in accordance with ISO 9001			

COMMERCIAL IN CONFIDENCE, THIS DOCUMENT IS THE PROPERTY OF AFL TELECOMMUNICATIONS LTD. AND IS TO BE HELD IN TRUST AND CONFIDENCE. PUBLICATION, DUPLICATION, DISCLOSURE OR USE FOR ANY PURPOSE NOT EXPRESSLY AUTHORISED IN WRITING BY AFL IS PROHIBITED.

© AFL Telecommunications Europe Ltd. Reg. UK 3971894 Newcombe Drive Hawksworth Swindon SN2 1DZ Tel: +44 (0)1793 647200. ISO 9001 & 14001 accredited. Specifications are subject to change without notice. Issued May 2014

www.**afl**global.com