

TWIN Audio/Video-Modulator | mono | UHF

TWIN Audio/video modulator | mono | UHF

- ✓ Moduliert zwei A/V-Signale in zwei HF-Signale, PAL B/G
- ✓ CCD-Überwachungskameras, Videokameras etc. anschließbar
- ✓ UHF-Kanal wählbar
- ✓ Aktive HF-Durchschleifung
- ✓ Ausgangspegel einstellbar
- ✓ LED-Display zur Kanalanzeige
- ✓ Inkl. Steckernetzteil
- ✓ Modulates two AV signals into two RF signals, PAL B/G
- ✓ CCD camera, video camera etc. can be connected
- ✓ UHF channel can be chosen
- ✓ Active RF-loop through
- ✓ Output level adjustable
- ✓ LED display for channel indication
- ✓ With plug-in power supply



Artikel Article	AVM 3-00
Artikelnummer Part No.	AVM00300
Verpackungseinheit Packing unit	1



Frequenzbereich Frequency range	470...862 MHz
Übertragungsnorm Transmission norm	PAL BG / PAL I / SECAM L
Durchgangsverstärkung Through gain	2...4 dB
Ausgangspegel, einstellbar Output level, adjustable	70...90 dBμV
Video Eingangsimpedanz Video input impedance	75 Ohm
Audio Eingangsimpedanz Audio input impedance	10 kOhm
Video Eingangspegel Video input level	1 V _{SS}
Audio Eingangspegel Audio input level	1 V _{SS}
Anschlüsse HF RF connectors	F-Buchse F-female
Anschlüsse Audio/Video Connectors Audio/video	RCA/Cinch + SCART
Steckernetzteil Power supply	230 V ~ 50 Hz/3W 6V=500 mA
Maße (B x H x T) ca. Dimensions (W x H x D) appr.	190 x 170 x 40 mm

