

Data sheet

Consolidation Point splice 6xSC-D APC OS2 (ceramic, green), pigtailed placed

Page 1/5

P/N

150309F206-E

EAN 4251122197185


2019/08/20

Version: P


Illustrations



Master



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- Consolidation Point splice equipped
 - Equipped with SC-D adapters, pigtailed and splice tray with crimp splice protection holders
 - To splice loose tube cables
 - Wall-mount powder-coated steel-sheet housing, (white, RAL 9010)
 - Patch area with swing-open and removable cover with label field
 - Possibility for strain relief for patch cord
 - Not used cutouts are closed by blind plugs
 - Cable management area with separate cover
 - Possible cable entry on the back side for one PG16 cable gland
 - If necessary order extensions or reductions for the fixing of the VIKs as separate accessory
 - Supplied with material for wall-mounting
-
- Variants: equipped with 6 SC-D adapters and pigtailed, all blue (OS2), lime green (OM5), violet (OM4), aqua (OM3) or 6 SC-D APC adapters and pigtailed, all green (OS2)

P | Cabling

Data sheet

Page 2/5

Consolidation Point splice 6xSC-D APC OS2 (ceramic, green), pigtails placed

P/N

150309F206-E

EAN 4251122197185

2019/08/20

Version: P

Technical Data

General Data

Fields of application

Structured building cabling, Office
Fiber to the Desk, Data center

Transmission technology

Fiber optic

Color

green

Dimensions

Dimension (L x W x H)

128.2 mm x 29.6 mm x 339 mm

Dimension (L x W x H)

5.047 in. x 1.165 in. x 13.346 in.

Number of cables/ cores

12

Cable Type

pigtail(s)

Fiber class

OS2 (IEC 60793-2-50 B1.3, B6_a & ITU-T G.657.A1, G.652.D)

Mode type of the fiber

Single mode

Shape

APC (Angled Physical Contact)

Fiber construction

9/125 µm

Labeling option

label strip / labeling strip

Connections/interfaces

Connector technology interface 1

SC-D Couplers

Connector technology interface 2

SC-D Couplers

Number of ports interface 1

6

Number of ports interface 2

6

Number of equipped ports interface 1

6

Number of ports interface 2 equipped

6

Number of ports with dust protection interface 2

6

Semi-tight buffered fiber pigtail length

2 m

Semi-tight buffered fiber pigtail diameter

0.9 mm

Cable access/outlet

possibility for cable entry on the back

Optical characteristics

Insertion loss

max. 0.4 dB dB

Return loss

min. 35 dB dB

Data sheet

Page 3/5

Consolidation Point splice 6xSC-D APC OS2 (ceramic, green), pigtails placed

P/N

150309F206-E

EAN 4251122197185

2019/08/20

Version: P

Technical Data

Mechanical characteristics

Connector type	duplex
strain relief	yes

Materials and material properties

Material - Housing	sheet steel
Material - Housing finish	powder-coated
Material - Sleeve	ceramic, slotted
RoHS	compliant

The product meets the following standards

Fibre optic connector interfaces	IEC 61754-4
Optical fibers: Indoor optical cables	
Sectional specification for class B single-mode fibres	ISO/IEC 60793-2-50 type B.1.3 & B6_a
Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
Fibre optic interconnecting devices and passive components	IEC 61300-3-4
Fibre optic interconnecting devices and passive components	IEC 61300-3-6
Fibre optic interconnecting devices and passive components	IEC 61300-3-35
Standard colours for insulation for low-frequency cables & wires	IEC 60304
ITU-T standard	ITU-T G.657.A1 compatible with ITU-T G.652.D

Classifications

ETIM 6.0	EC001130
ETIM 7.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
Packaging dimension	470 mm x 200 mm x 60 mm
Packaging dimension	18.504 in. x 7.874 in. x 2.362 in.



Data sheet

Page 4/5

Consolidation Point splice 6xSC-D APC OS2 (ceramic, green), pigtailed placed

P/N

150309F206-E

EAN 4251122197185

2019/08/20

Version: P

Accessories

P/N	Designation
150811P1611-E	Thread reducer PG16 to PG11
150811P1613-E	Thread reducer PG16 to PG13.5
150811P1621-E	Thread enlarger PG16 to PG21
15090401-E	OpDAT crimp splice protection (12 pcs)
15090401-I	OpDAT crimp splice protection (150 pcs)



P | Cabling

Data sheet

Page 5/5

Consolidation Point splice 6xSC-D APC OS2 (ceramic, green), pigtailed placed

P/N

150309F206-E

EAN 4251122197185

2019/08/20

Version: P

Illustrations

Dimensional drawing

