MK-6 SPLICE BOX

FEATURES:

- wall mounted in controlled environments
- easy high fibre count cables branching out to small fibre count cables
- entry cable outer diameter range: 10 mm to 18 mm
- branch cable outer diameter range: 8 mm to 12 mm
- full front access to splice trays

THE SET INCLUDES:

- KS-24 splice trays (full amount - option)
- cable glands DP 13, DP 16, DP 21
- cable ties, cable organisers
- installation and handling instructions
- installation kit


TECHNICAL SPECIFICATIONS:

	MK-6/72	MK-6/144
number of splice trays	3 x KS-24 (max. 9 x KS-24)	6 x KS-24 (max. 18 x KS-24)
number of splices	72 (max. 216)	144 (max. 432)
number of cable inputs/outputs	2/24	4/40
maximum cable diameter [mm]	4 dla ø18 i 22 dla ø12	2 dla ø18 i 42 dla ø12
dimensions: width/height/depth [mm]	470/120/430	820/120/430
housing material/colour	steel sheet/RAL 7035	
mechanical protection IK	IK 08	
environmental protection IP	IP51	


ORDERING:

MK-6/72 - Splice Box for 72 fibre splices

TELECOM ACCESS CATV LAN FTTx PON



Splice Box MK-6/72



Splice Box MK-6/144