

# MegaLine<sup>®</sup> patch cord

## RJ45 - RJ45 - 10.0 m

Cat. 5, class D, with -cable sheet



Illustration similar

### Description

The cable type used is suitable for transmission frequencies of up to 100 MHz. The pair shielding and the high-coverage copper braiding as overall shielding ensure excellent NEXT and return loss values.

The patch and connection cables are fitted at both ends with a shielded Hirose<sup>®</sup> TM11 RJ45 plug and boot. The "superflex" version is excellent for demanding industrial applications (e.g. drag chains).

### Properties / applications

IEEE 802.3, 10Base-T, 100Base-T, 1000Base-T  
 IEEE 802.5 16MB, ISDN, FDDI, ATM

### Construction

Colour of sheath Colza yellow

Kink protection colour Yellow

Wiring 1:1

### Electrical characteristics

Category 5

Class D

Wiring 1:1

### Fire characteristics (cable)

Fire load 0.7 MJ/m

### Standards, certificates and approvals

Connector standard EN 60603-7

Cabling standard EN 50173, ISO/IEC 11801

Flame retardancy IEC 60332-2-2

Halogen-free IEC 60754-1/2

Smoke density IEC 61034-1/2

Oil resistance IEC 60811-2-1 with test-oil IRM 902 (acc. to ISO 1817) at +70°C; 4 h; pulling rate 50 mm/min  
 relative change of the elongation at break and tensile strength  
 max. +/- 40 %

Chemical continuance Free of hazardous substances  
 acc. to RoHS 2011/65/EU, Good  
 resistance to oil, petrol, acid and  
 leach

# MegaLine<sup>®</sup> patch cord

## RJ45 - RJ45 - 10.0 m

Cat. 5, class D, with -cable sheet

Part number	Cable length (m)	Cable length (m)	Weight approx.	Colour of sheath
LKD9AA700840000	10.0	10.0	0.63	Colza yellow