

BAB 1-16P 1-way tap | 16 dB | 5...1218 MHz



- ✓ High return loss
- ✓ For multimedia-use
- ✓ Inputs and outputs hum-suppressed
- ✓ High intermodulation suppression
- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Return loss and isolation according to VKFD TS 220
- ✓ Vodafone Kabel Deutschland approved

Order information

Type	BAB 1-16P
Order no.	BAB00116P
GTIN	7611682005684
PE	1
VE	1
EU customs tariff number	85291080



Technical data

Frequency range	5...1218 MHz
Intermodulation ratio (EN 60728-4)	118 dB μ V
Tap loss	
5...94 MHz	≤ 16.8 dB
94...188 MHz	≤ 16.7 dB
188...376 MHz	≤ 16.7 dB
376...752 MHz	≤ 16.8 dB
752...950 MHz	≤ 16.9 dB
950...1218 MHz	≤ 17.4 dB
Through loss	
5...94 MHz	≤ 0.4 dB
94...188 MHz	≤ 0.4 dB
188...376 MHz	≤ 0.5 dB
376...752 MHz	≤ 0.6 dB
752...950 MHz	≤ 0.8 dB
950...1218 MHz	≤ 1.1 dB
Return loss	
5...94 MHz	≥ 18 dB
94...188 MHz	≥ 16.5 dB
188...376 MHz	≥ 15 dB
376...752 MHz	≥ 13.5 dB
752...1218 MHz	≥ 12 dB
Connectors	
Connector type	F
General	
Dimensions (W × H × D) appr.	67 × 55 × 30 mm
Weight	0.045 kg