

BAB 6-02P 6-way terminal tap | 13.0...15.5 dB | 5...1218 MHz


- ✓ High return loss
- ✓ For multimedia-use
- ✓ Inputs hum-suppressed
- ✓ High intermodulation suppression
- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Return loss and isolation according to VFCD TS 220
- ✓ Vodafone Kabel Deutschland approved

Order information

Type	BAB 6-02P
Order no.	BAB00602P
GTIN	7611682006346
PE	1
VE	1
EU customs tariff number	85291080


Technical data

Frequency range	5...1218 MHz
Intermodulation ratio (EN 60728-4)	120 dBμV
Taps	6
Tap loss	
Tap 1	13.0 ±2.5 dB
Tap 2	13.0 ±2.5 dB
Tap 3	14.5 ±2.5 dB
Tap 4	14.5 ±2.5 dB
Tap 5	15.5 ±2.5 dB
Tap 6	15.5 ±2.5 dB
Return loss	
5...40 MHz	≥ 18 dB
40...470 MHz	≥ 18 dB
470...862 MHz	≥ 16 dB
862...1006 MHz	≥ 14 dB
1006...1300 MHz	≥ 14 dB
Isolation	
Tap-tap @ 5...40 MHz	≥ 30 dB
Tap-tap @ 40...470 MHz	≥ 32 dB
Tap-tap @ 470...862 MHz	≥ 30 dB
Tap-tap @ 862...1006 MHz	≥ 30 dB
Tap-tap @ 1006...1300 MHz	≥ 25 dB
Connectors	
Connector type	F
General	
Dimensions (W × H × D) appr.	93 × 54 × 39 mm
Weight	0.175 kg