

## SKB 11-13 RG11 Coaxial cable CATV | SAT | 300 m



- ✓ 3-way shielded
- ✓ Class A++ according to EN 50117-2-3
- ✓ Screening factor  $\geq 105$  dB @ 30...1000 MHz
- ✓ Coupling resistance  $\leq 0.9$  m $\Omega$ /m @ 5...30 MHz
- ✓ Inner conductor made of solid copper, diameter 1.63 mm
- ✓ Physically-foamed dielectric, diameter 7.4 mm
- ✓ Screening alum. foil, tinned copper braiding, alum. foil
- ✓ Jacket PE, black
- ✓ UV resistant
- ✓ Degressive metering
- ✓ Fire behavior Fca acc. to EN 50575
- ✓ Suitable for underground installation in a ductwork for cables
- ✓ 300 m on wooden drum
- ✓ Compression plug, compression tool and stripping tool available on request.

## Order information

|                          |               |
|--------------------------|---------------|
| Type                     | SKB 11-13     |
| Order no.                | SKB01113      |
| GTIN                     | 7611682007756 |
| PE                       | 1             |
| VE                       | 1             |
| EU customs tariff number | 85442000      |



## Technical data

## Electrical data

|                     |  |
|---------------------|--|
| Impedance           | 75 Ohm   |
| Attenuation         | 5.4 dB / 100 m @ 200 MHz<br>13.5 dB / 100 m @ 1000 MHz<br>22.0 dB / 100 m @ 2400 MHz |
| Screening factor    | >105 dB @ 30...1000 MHz<br>>95 dB @ 1000...2000 MHz<br>>85 dB @ 2000...3000 MHz      |
| Coupling resistance | <0.9 m $\Omega$ /m @ 5...30 MHz  |

## Mechanical data

|                                     |                     |
|-------------------------------------|---------------------|
| Inner conductor material   diameter | Cu   1.63 mm        |
| Dielectric diameter                 | 7.3 mm              |
| Braiding   opt. coverage            | 144 x 0.15 mm   85% |
| Jacket material   diameter          | PE   10.3 mm        |
| Bending radius single   multiple    | 36   100 mm         |

## General

|                               |                   |
|-------------------------------|-------------------|
| Application temperature range | -5...+50°C        |
| Operating temperature range   | -40° C ... +85° C |
| Fire behavior                 | Fca               |

## Suitable products

[CFS 7-00 F | male crimp type](#)

[CFS 7-02 F | male screw type](#)