

P | Cabling

Data sheet

OpDAT slide patch panel splice
6xSC-D (beige), OM2, gray

Page 1/6

P/N

150262B206-E

EAN 4250184166566


2021/10/04

Version: Z

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel with pull-out splice tray / front cover (gray or black)
- equipped with SC-D adapters and SC pigtails
- pigtails with semi-tight buffered fiber dia. 0.9 mm, 12 colors, secondary and primary coating in the same color, length 2.0 m
- pigtails inserted and stripped in standard splice trays with crimp splice holders
- pigtails are cleaned and plugged in adapters
- splice tray can be tilted and removed completely for better mounting
- unused cutouts are closed by blank plugs
- straight cable entry from the left and right on the rear, with enclosed PG16 cable gland
- a PG16 mounting kit is included in delivery
- variants: equipped with 6, 12 or 24 SC-D adapters and pigtails, all blue (OS2), lime green (OM5), violet (OM4), aqua (OM3) or made of metal (OM2) or SC-D APC adapters, all green (OS2)



P | Cabling

Data sheet

Page 2/6

OpDAT slide patch panel splice 6xSC-D (beige), OM2, gray

P/N

150262B206-E

EAN 4250184166566

2021/10/04

Version: Z

Technical Data

General Data

Fields of application

	Structured building cabling, Office Data center
Design	patch panel
Mounting style	1RU
Transmission technology	Fiber optic
Port numbering	yes
Color	beige
Dimensions	
Dimension (L x W x H)	244 mm x 482.6 mm x 44.45 mm
Dimension (L x W x H)	9.606 in. x 19 in. x 1.75 in.
Inches	19 inches
Height unit	1RU
Installation depth	240 mm
Installation depth	9.449 in.
Number of cables/ buffered fibers	12
Cable Type	pigtail(s)
Fiber class	OM2: ISO/IEC 11801/EN 50173 & IEC 60793-2-10/EN 60793-2-10 A1.a.1
Mode type of the fiber	Multimode
Fiber construction	50/125 µm
Labeling option	printed numbers

Connections/interfaces

Connector technology interface 1	SC-D Couplers
Connector technology interface 2	SC-D Couplers
Number of ports interface 1	24
Number of ports interface 2	24
Number of equipped ports interface 1	6
Number of ports interface 2 equipped	6
Number of ports with dust protection interface 2	6
Number of blind	18
Semi-tight buffered fiber pigtail length	2 m
Semi-tight buffered fiber pigtail length	6.56 ft



P | Cabling

Data sheet

Page 3/6

OpDAT slide patch panel splice 6xSC-D (beige), OM2, gray

P/N

150262B206-E

EAN 4250184166566

2021/10/04

Version: Z

Technical Data

Connections/interfaces

Semi-tight buffered fiber pigtail diameter	0.9 mm
Semi-tight buffered fiber pigtail diameter	0.035 in.
Cable access/outlet	several possibilities for cable entry on the back

Optical characteristics

Insertion loss	max. 0,4 dB
Return loss	min. 35 dB

Mechanical data

Cut-out	SC-D, LC-Q, ST-D
Connector type	duplex
Life - Number of mating cycles	min. 1000
strain relief	yes

Materials and material properties

Material - Housing	Al (Aluminium)
Material - Front cover	sheet steel
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics
RoHS	compliant

The product meets the following standards

Optical fibers: Product specifications	
Sectional specification for category A1 multimode fibres	ISO/IEC 60793-2-10 (A1a.1)
Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
Fibre optic interconnecting devices and passive components	IEC 61300-3-4
Fibre optic interconnecting devices and passive components	IEC 61300-3-6
Fibre optic interconnecting devices and passive components	IEC 61300-3-35
Standard colours for insulation for low-frequency cables & wires	IEC 60304



P | Cabling

Data sheet

Page 4/6

OpDAT slide patch panel splice 6xSC-D (beige), OM2, gray

P/N

150262B206-E

EAN 4250184166566

2021/10/04

Version: Z

Technical Data

Classifications

ETIM 5.0	EC001130
ETIM 6.0	EC001130
ETIM 7.0	EC001130
ETIM 8.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
Packaging unit - Weight (gram)	1700 g
Packaging unit - Weight (pound)	3.75 lb
Packaging dimension	523 mm x 361 mm x 45 mm
Packaging dimension	20.591 in. x 14.213 in. x 1.772 in.



P | Cabling

Data sheet

Page 5/6

OpDAT slide patch panel splice 6xSC-D (beige), OM2, gray

P/N

150262B206-E

EAN 4250184166566

2021/10/04

Version: Z

Accessories

P/N	Designation
130792	Mounting kit, cage nuts M6
150811M20-E	Cable gland M20 (Clamping range 7 to 12 mm)
150811M25-E	Cable gland M25
15090301-I	OpDAT splice protection cover for 12 crimp splices
15090401-E	OpDAT crimp splice protection (12 pcs)



P | Cabling

Data sheet

Page 6/6

OpDAT slide patch panel splice
6xSC-D (beige), OM2, gray

P/N

150262B206-E

EAN 4250184166566

2021/10/04

Version: Z

Illustrations

Dimensional drawing

