

Data sheet


OpDAT fix patch panel VIK
12xSC-D (beige), OM2, gray

Page 1/4


P/N
150250B212-E
 EAN 4250184126751

2018-13-03

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel for fixed installation
- equipped with SC-D adapters
- prepared for fixation of pre-terminated installation cables (OpDAT VIK)
- light aluminium construction with steel sheet front plate painted (gray or black)
- unoccupied recesses are closed with blind plugs
- removable front plate for easy adapter mounting
- screwed on cover for easy access during service work
- several possibilities for cable entry on the back (fastening with PG13.5, PG16 and PG21 or M20 and M25)
- toolless fastening of pre-assembled installation cables (OpDAT VIK) in a U-shaped cutout
- variants: equipped with 6, 12 or 24 SC-D adapters, all blue (OS2), lime green (OM5), violet (OM4), aqua (OM3) or 6, 12 or 24 SC-D APC adapters, all green (OS2)



P | Cabling

Data sheet

OpDAT fix patch panel VIK 12xSC-D (beige), OM2, gray

Page 2/4

P/N

150250B212-E

EAN 4250184126751

2018-13-03

Technical Data

General Data

Fields of application

Structured building cabling, Office
Data center

Design patch panel

Mounting style 1RU

Transmission technology Fiber optic

Port numbering yes

Color beige

Dimensions

Dimension (L x W x H) 242.50 x 482.60 x 44.45 mm

Dimension (L x W x H) 9.547 x 19.00 x 1.75 in.

Inches 19 inches

Height unit 1RU

Installation depth 243.00 mm

Installation depth 9.567 in.

Fiber class OM2: ISO/IEC 11801/EN 50173 & IEC 60793-2-10/EN
60793-2-10 A1.a.1

Mode type of the fiber Multimode

Fiber construction 50/125 µm

Labeling option printed numbers

Connections/interfaces

Connector technology interface 1 SC-D Couplers

Connector technology interface 2 SC-D Couplers

Number of ports interface 1 24

Number of ports interface 2 24

Number of equipped ports interface 1 12

Number of equipped ports interface 2 12

Number of ports with dust protection interface 1 12

Number of ports with dust protection interface 2 12

Number of blind covers interface 2 12

Cable access/outlet several possibilities for cable entry on the back



Data sheet

Page 3/4

OpDAT fix patch panel VIK 12xSC-D (beige), OM2, gray

P/N

150250B212-E

EAN 4250184126751

2018-13-03

Technical Data

Mechanical characteristics

Cut-out	SC-D, LC-Q, ST-D
Connector type	Duplex
Life - Number of mating cycles	min. 1000
strain relief	yes

Materials and material properties

Material - Housing	Al (Aluminium)
Material - Front cover	sheet steel
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics

Approvals

RoHS	compliant
------	-----------

The product meets the following standards

Fibre optic connector interfaces	DIN EN 61754-4
----------------------------------	----------------

Classifications

ETIM 5.0	EC001130
ETIM 6.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
Packaging dimension (W x H x D)	580.00 x 405.00 x 70.00 mm
Packaging dimension (W x H x D)	22.835 x 15.945 x 2.756 in.



P | Cabling

Data sheet

OpDAT fix patch panel VIK 12xSC-D (beige), OM2, gray

Page 4/4

P/N

150250B212-E

EAN 4250184126751

2018-13-03

Illustrations

Dimensional drawing

