

BAB 1-06P 1-way tap | 6 dB | 5...1218 MHz



- ✓ High return loss
- ✓ For multimedia-use
- ✓ Inputs and outputs hum-suppressed
- ✓ High intermodulation suppression
- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Return loss and isolation according to VKFD TS 220
- ✓ Vodafone Kabel Deutschland approved

Order information

Type	BAB 1-06P
Order no.	BAB00106P
GTIN	7611682005646
PE	1
VE	1
EU customs tariff number	85291080



Technical data

Frequency range	5...1218 MHz
Intermodulation ratio (EN 60728-4)	120 dBμV
Tap loss	
5...94 MHz	≤ 7.8 dB
94...188 MHz	≤ 6.1 dB
188...376 MHz	≤ 6.2 dB
376...752 MHz	≤ 6.5 dB
752...950 MHz	≤ 6.4 dB
950...1218 MHz	≤ 6.3 dB
Through loss	
5...94 MHz	≤ 2.1 dB
94...188 MHz	≤ 2.2 dB
188...376 MHz	≤ 2.2 dB
376...752 MHz	≤ 2.3 dB
752...950 MHz	≤ 2.5 dB
950...1218 MHz	≤ 3.4 dB
Return loss	
5...94 MHz	≥ 18 dB
94...188 MHz	≥ 16.5 dB
188...376 MHz	≥ 15 dB
376...752 MHz	≥ 13.5 dB
752...1218 MHz	≥ 12 dB
Connectors	
Connector type	F
General	
Dimensions (W × H × D) appr.	67 × 55 × 30 mm
Weight	0.045 kg