

## QEW 5-06 Erdungswinkel | einreihig | Überspannungsschutz



- ✓ 5-way
- ✓ Earthing and equipotential bonding acc. to EN 60728-11
- ✓ For AXING multiswitches SPU/SES 5xx-06 at input
- ✓ Incl. surge protection devices SZU 6-02
- ✓ With premium-line double F-sockets CFA 26-02 and quickfix adapter CFA 4-01

### Order information

|                          |               |
|--------------------------|---------------|
| Type                     | QEW 5-06      |
| Order no.                | QEW00506      |
| GTIN                     | 7611682006674 |
| PE                       | 1             |
| VE                       | 1             |
| EU customs tariff number | 85366910      |

**Wide Band**  
approved - 2.4 GHz

### Technical data

|                                     |                         |
|-------------------------------------|-------------------------|
| Application                         | SPU 5xx-06 / SES 5xx-06 |
| Screening factor acc. to EN 50083-2 | > 90 dB                 |
| Frequency range                     | 5...2500 MHz            |
| Through loss                        | ≤ 0.5 dB                |
| DC power pass                       | yes                     |
| Max. through current                | 0.5 A @ 30 VDC          |
| Impulse discharge current           | 5 kA @ 8/20 µs          |
| <b>Connectors</b>                   |                         |
| Connector type                      | F                       |
| Number                              | 5                       |
| Return loss                         | 20 dB -1.5dB/Okt.       |
| <b>General</b>                      |                         |
| Material                            | surface treated         |
| Weight                              | 0.352 kg                |