

SKB 11-03 RG11 Coaxial cable CATV | SAT



- ✓ Suitable for underground installation in a ductwork for cables
- ✓ Fire behavior Fca acc. to EN 50575
- ✓ Inner conductor StCu, diameter 1.63 mm
- ✓ Physically-foamed dielectric, diameter 7.4 mm
- ✓ Screening alum. foil and tinned copper braiding
- ✓ Jacket PE, black
- ✓ UV resistant
- ✓ Degressive metering
- ✓ 300 m on wooden drum

Order information

Type	SKB 11-03
Order no.	SKB01103
GTIN	7611682110128
PE	1
VE	1
EU customs tariff number	85442000



Technical data

Electrical data

Impedance	75 Ω
Attenuation	5.3 dB / 100 m @ 200 MHz 11.4 dB / 100 m @ 800 MHz 20.8 dB / 100 m @ 2400 MHz
Screening factor	>90 dB @ 30...1000 MHz >85 dB @ 1000...2000 MHz >80 dB @ 2000...3000 MHz

Mechanical data

Inner conductor material diameter	StCu 1.63 mm
Dielectric diameter	7.4 mm
Braiding opt. coverage	96 x 0.15 mm 60%
Jacket material diameter	PE 10.4 mm
Bending radius single multiple	38 mm 100 mm

General

Application temperature range	-5...+50°C
Operating temperature range	-20...+75°C
Fire behavior	Fca
Weight	22.960 kg

Suitable products

[CFS 7-00 F | male crimp type](#)

[CFS 7-02 F | male screw type](#)