

## SKB 395-01 Coaxial cable | 3-way shielded



- ✓ For SAT or CATV indoor installation
- ✓ Class A+ according to EN 50117-2-4
- ✓ Fire behavior Eca acc. to EN 50575
- ✓ Inner conductor StCu, diameter 1.02 mm
- ✓ Physically-foamed dielectric, diameter 4.6 mm
- ✓ Screening aluminium foil, bonded/aluminium braiding/aluminium foil
- ✓ Jacket PVC, white
- ✓ UV resistant
- ✓ Degressive metering
- ✓ 100 m on a cardboard spool

## Order information

|                          |               |
|--------------------------|---------------|
| Type                     | SKB 395-01    |
| Order no.                | SKB39501      |
| GTIN                     | 7611682113952 |
| PE                       | 1             |
| VE                       | 4             |
| EU customs tariff number | 85442000      |



## Technical data

|                                     |                                                                                     |
|-------------------------------------|-------------------------------------------------------------------------------------|
| Electrical data                     |                                                                                     |
| Impedance                           | 75 Ω                                                                                |
| Attenuation                         | 8.7 dB / 100 m @ 200 MHz<br>18.0 dB / 100 m @ 800 MHz<br>32.9 dB / 100 m @ 2400 MHz |
| Screening factor                    | >100 dB @ 30...1000 MHz<br>>100 dB @ 1000...2000 MHz<br>>100 dB @ 2000...3000 MHz   |
| Coupling resistance                 | <2.5mOhm/m                                                                          |
| Mechanical data                     |                                                                                     |
| Inner conductor material   diameter | StCu   1.02 mm                                                                      |
| Dielectric diameter                 | 4.6 mm                                                                              |
| Braiding   opt. coverage            | 80 x 0.12 mm   55%                                                                  |
| Jacket material   diameter          | PVC   6.8 mm                                                                        |
| Bending radius single   multiple    | 24 mm   68 mm                                                                       |
| General                             |                                                                                     |
| Application temperature range       | -5...+50°C                                                                          |
| Operating temperature range         | -20...+75°C                                                                         |
| Fire behavior                       | Eca                                                                                 |
| Weight                              | 3.805 kg                                                                            |

## Suitable products

[SKA 1-00 Cable dispenser](#)  
[CKS 7-48 IEC | male | compression](#)  
[CKK 7-48 IEC | female | compression](#)  
[CFS 97-48 F | male | compression](#)  
[CFS 99-48 F | male | compression | Quickfix](#)  
[CFS 100-48 F | male | compression | Quickfix](#)  
[CFS 93-48 F | Opti-fix | male | self compression](#)  
[SZU 11-01 Water protection sleeve](#)