

TZU 40-03 EoC inserter | 4 dB



- ✓ For feeding in RF-modulated IP signals
- ✓ 5...1006 MHz | 85...1006 MHz (with 85 MHz high-pass filter)
- ✓ 4 dB EoC loss between connector "EoC" and connector "Eingang/Ausgang"
- ✓ 4 dB through loss between the connector "terr. Signale" and the connector "Eingang/Ausgang"
- ✓ Connection 1: terr. Signale
- ✓ Connection 2: EoC
- ✓ Connection 3: Eingang/Ausgang

Order information

Type	TZU 40-03
Order no.	TZU04003
GTIN	7611682003475
PE	1
VE	1
EU customs tariff number	85291080



Technical data

Application	EoC
Frequency range	5...1006 MHz 85...1006 MHz
EoC loss	4 dB
Through loss	4 dB
Connectors	
Connector 1	F-female
Connector 2	F-female
Connector 3	F-male, quickfix
General	
Dimensions (W × H × D) appr.	55 × 34 × 18 mm
Weight	0.029 kg

Suitable products

[EOC 1-31 Ethernet over Coax | Peer-to-Peer | 720 Mbps](#)
[EOC 2-31 Ethernet over Coax | Peer-to-Peer | 720 Mbps | WiFi](#)
[EOC 20-01 Ethernet over Coax | Master | 720 Mbps](#)
[EOC 20-02 Ethernet over Coax | Endpoint | 720 Mbps](#)