

Data sheet

OpDAT fix patch panel splice
24xST-D (metal), OM3, gray

Page 1/5


P/N
150255D124-E
 EAN 4251122178290

2018-13-03

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel for fixed installation
- equipped with ST-D adapters and ST pigtails
- pigtails with semi-tight buffered fiber dia. 0.9 mm, 12 colors, secondary and primary coating in the same color, length 2.0 m
- pigtails inserted and stripped in standard splice trays with crimp splice holders
- pigtails are cleaned and plugged in adapters
- light aluminum construction with steel sheet front plate painted (gray or black)
- unoccupied recesses are closed with blind plugs
- removable front plate for easy adapter mounting
- screwed on cover for easy access during service work
- several possibilities for cable entry on the back (fastening with PG13.5, PG16 and PG21 or M20 and M25)
- supplied with one PG16 cable gland
- Variants: equipped with 6, 12 or 24 ST-D adapters and pigtails each made of metal (OS2, OM4 oder OM3)



Data sheet

OpDAT fix patch panel splice 24xST-D (metal), OM3, gray

Page 2/5

P/N

150255D124-E

EAN 4251122178290

2018-13-03

Technical Data

General Data

Fields of application

	Structured building cabling, Office Data center
Design	patch panel
Mounting style	1RU
Transmission technology	Fiber optic
Port numbering	yes
Color	metallike
Dimensions	
Dimension (L x W x H)	242.50 x 482.60 x 44.45 mm
Dimension (L x W x H)	9.547 x 19.00 x 1.75 in.
Inches	19 inches
Height unit	1RU
Installation depth	243.00 mm
Installation depth	9.567 in.
Number of cables/ cores	48
Cable Type	pigtail(s)
Fiber class	OM3: ISO/IEC 11801/EN 50173 & IEC 60793-2-10/EN 60793-2-10 A1.a.2
Mode type of the fiber	Multimode
Fiber construction	50/125 µm
Labeling option	printed numbers

Connections/interfaces

Connector technology interface 1	ST-D Couplers
Connector technology interface 2	ST-D Couplers
Number of ports interface 1	24
Number of ports interface 2	24
Number of equipped ports interface 1	6
Number of equipped ports interface 2	6
Number of ports with dust protection interface 2	6
Number of blind covers interface 2	18
Semi-tight buffered fiber pigtail length	2.00 m
Semi-tight buffered fiber pigtail length	6.56 ft
Semi-tight buffered fiber pigtail diameter	0.90 mm
Semi-tight buffered fiber pigtail diameter	0.035 in.



Data sheet

Page 3/5

OpDAT fix patch panel splice 24xST-D (metal), OM3, gray

P/N

150255D124-E

EAN 4251122178290

2018-13-03

Technical Data

Connections/interfaces

Cable access/outlet	several possibilities for cable entry on the back
---------------------	---

Optical characteristics

Insertion loss	max. 0.4 dB
----------------	-------------

Return loss	min. 35 dB
-------------	------------

Mechanical characteristics

Cut-out	SC-D, LC-Q, ST-D
---------	------------------

Connector type	Duplex
----------------	--------

Life - Number of mating cycles	min. 1000
--------------------------------	-----------

strain relief	yes
---------------	-----

Materials and material properties

Material - Housing	Al (Aluminium)
--------------------	----------------

Material - Front cover	sheet steel
------------------------	-------------

Material - Sleeve	ceramic, slotted
-------------------	------------------

Material - Coupler housing	metal
----------------------------	-------

Approvals

RoHS	compliant
------	-----------

The product meets the following standards

Fibre optic connector interfaces	DIN EN 61754-2
----------------------------------	----------------

Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
--	--

Fibre optic interconnecting devices and passive components	IEC 61300-3-4
--	---------------

Fibre optic interconnecting devices and passive components	IEC 61300-3-6
--	---------------

Fibre optic interconnecting devices and passive components	IEC 61300-3-35
--	----------------

Standard colours for insulation for low-frequency cables & wires	IEC 60304
--	-----------



Data sheet

Page 4/5

OpDAT fix patch panel splice 24xST-D (metal), OM3, gray

P/N

150255D124-E

EAN 4251122178290

2018-13-03

Technical Data

Classifications

ETIM 5.0	EC001130
ETIM 6.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
Packaging dimension (W x H x D)	523.00 x 361.00 x 45.00 mm
Packaging dimension (W x H x D)	20.591 x 14.213 x 1.772 in.



P | Cabling

Data sheet

OpDAT fix patch panel splice 24xST-D (metal), OM3, gray

Page 5/5

P/N

150255D124-E

EAN 4251122178290

2018-13-03

Illustrations

Dimensional drawing

