UKGMPUCSM



Ultra Low Loss Singlemode MPO12 Female to Unconnectorized 144-Fiber Pre-terminated Trunk Cable, Rollable Ribbon Indoor/Outdoor Armored Central Tube, Low Smoke Zero Halogen/Riser

Product Classification

Regional Availability

Asia | Australia/New Zealand | Europe | Latin America | Middle East

/Africa | North America

Portfolio CommScope®

Product Type Fiber trunk cable assembly

Product Brand SYSTIMAX ULL | SYSTIMAX ULL

Ordering Note For additional jacket colors, please contact a CommScope Sales Representative | For

lengths greater than 999 ft (304 m), orders must be in meters | Minimum length may

vary based on cable configuration

General Specifications

Color, boot A Black
Color, connector A Green

Construction Type Armored | Rollable ribbon

Fibers per Subunit, quantity 12

Furcation Color Yellow

 Interface, Connector A
 MPO-12/APC

 Interface, Connector B
 Unterminated

Jacket Color Black

Polarity Method B Enhanced

Total Fibers, quantity 144

Dimensions

Breakout Length 33 in

Cable Assembly Length, minimum (ft) 10

Cable Assembly Length, maximum (ft) 999


Cable Assembly Length, minimum (m) 3

Cable Assembly Length, maximum (m) 999



UKGMPUCSM

Ordering Tree



Mechanical Specifications

Cable Retention Strength, maximum 11.24 lb @ 0 $^{\circ}$ | 4.40 lb @ 90 $^{\circ}$

Optical Specifications

Fiber Mode Singlemode

Fiber Type G.657.A2, TeraSPEED®

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \text{ (+14 }^{\circ}\text{F to } +140 \,^{\circ}\text{F)}$

Environmental Space Dual Rated LSZH/Riser

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



Included Products

760239048 Z-144-CZ-RR-F12BK/8G1 /99G/B2 Indoor/Outdoor, Interlocking Armored, Low Smoke Zero Halogen (LSZH), Riser-Rated, Gel-Free, Central Tube Rollable Ribbon Cable

860638318 - MPO12, ULTRA LOW LOSS, FEMALE, SM, GREEN, 3mm

Page 2 of 3



UKGMPUCSM

