

HFTP Customer premises fiber wall outlet, SC/APC, no pigtails, one adapter

- Compact fiber wall outlet for use at the final fiber termination point in the customer premises
- Can be wall mounted and mounted on wall boxes with fixation points of 60mm
- Direct termination with field installable connectors
- Laser safe with in-built individual shutters

Product Classification

Regional Availability	EMEA
Product Type	Outlet
Product Series	HFTP
Minimum Order Quantity	300


General Specifications

Color	White
Cover Type	Screw-on
Interface Type	SC/APC
Mounting	Wall mount
Total Ports, quantity	1

Dimensions

Height	105.41 mm 4.15 in
Width	82.55 mm 3.25 in
Depth	23.876 mm 0.94 in

Outline Drawing



Material Specifications

Material TypeLSZH Thermoplastic

Optical Specifications

Fiber ModeSinglemode

Environmental Specifications

Storage Temperature-30 °C to +60 °C (-22 °F to +140 °F)

Relative HumidityUp to 93%, non-condensing

Environmental SpaceIndoor

Packaging and Weights

Packaging quantity10

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



Included Products

- | | | |
|----------------|---|--|
| CK7246-000 | – | HFTP Customer premises fiber wall outlet, no adapters, no pigtails, for splicing |
| HFTP-N0-NN00-E | | only |