

# Optical Fiber Fusion Splicer

AI-08 PRODUCT MANUAL

## OPTICAL FIBER FUSION SPLICER



Product Code.	70001-RT AI 08	
File Compiled Version	V1	
Product Name	OPTICAL FIBER FUSION SPLICER	



#### NEW PRODUCT LAUNCH



CLASSIC MASTERPIECE

Al-8 use the latest core alignment technology with auto focus and six motors, it is a new generation of fiber fusion splicer. It is fully qualified with trunk construction of medium and short distance, FTTH project, security monitoring and other fiber cable splicing projects. The machine uses industrial quad-core CPU, fast response, is currently one of the fastest fiber splicing machine in the market; with 5-inch 800X480 high-resolution screen, the operation is simple and intuitively; and up to 300 times focus magnifications, making it is very easy to observe the fiber with naked eyes. 5 seconds speed core alignment splicing, 16 seconds heating, the working efficiency increased by 50% compared to ordinary splicing machines. Under the conditions of rigorous testing, the performance is still outstanding; toolbox is small, exquisite, durable, and with unique bench design. The design of operating platform reflects the humanistic care; unique lighting design, it is convenient for night construction or repair. Screen brightness is adjustable and it is convenient for outdoor sunshine environment operation. The core parts are using imported brands, aviation metal body material with exquisite details. With the combination of advanced technology and design, the new generation of optical fiber fusion splicer will bring you a reliable and comfortable user experience.

#### MASTERPIECE HIGH-END LUXURY





5 seconds fast splicing

16 seconds fast heating

Disassembly free three-in-one fiber holder

300 times magnification auto focus

7800mAh large capacity battery

Once splicing reaches
 to 50,000 times free
 replacement a new machine

#### METAL BODY AESTHETIC DETAILS





- 18 patent results
- Lifetime free warranty

LED light Convenient for night operati

Battery press & remove



#### CORE PARTS QUALITY ASSURANCE









Siemens stepper motor

Roth ROUST linear guide

Sanyo lithium battery

Aviation metal material

#### THE TOOLBOX

COMES WITH A STOOL TO FACILITATE THE CONSTRUCTION WORKERS.





Remove the stool



Do not need to take out the splicer machine from the toolbox while working.





### Lighting for splicer

Convenient for night operation

We are so hard only for you









#### 3 IN 1 FIBER HOLDER

SM, MM, bare fiber, pigtail, rubber-insulated, multi fiber cable





#### THE BATTERY POPUP AUTOMATICALLY

7800 mA high-capacity lithium battery

- •charging time  $\leq 3.5$  hours
- •continuous splicing and

heating about 200 times





# CAN CHARGE THE PHONE

Intimate care, just understand you



If your phone is out of power at outdoor, our machine can charge your phone, ensure you can contact your family members or colleagues in time.



# SHOW GOOD PERFORMANCE IN PLATEAU, DESERT, AND EXTREME COLD ENVIRONMEN









## BASIC PARAMETER

Fiber alignment	Core/cladding alignment / Manual alignment	Built-in lighting	easy for night operation
Splicing time	6S	Tension Test	Standard 2N
Heating time	158	Fiber holders	3 in 1 fiber holder, SM, MM, bare fiber, pigtail, rubber-insulated, multi fiber cable
Heating mode	Automatic heating (Preheating)	Magnification	300 for X or Y view, 150 for X or Y view
Focus mode	Six motors Auto focus	Screen	5 inch TFT color display
Applicable Fibers	SM(G. 652&G. 657)、MM (G. 651)、DS(G. 657)、NZDS (G. 655)	Splicing Mode	Normal / high precision splicing
Splice Loss	0.025dB (SM) 、0.01dB (MM) 0.04dB (DS/NZDS)	Splicing method	Fully automatic, Step by step splicing
Control technology	Real-time control and calibration of fusion ARC	Splicing record storage	Synchronize to the phone, the server to cloud storage unlimited
Return loss	Better than 60DB	Built-in battery	7800 mA high-capacity lithium battery, charging time ≤ 3.5 hours, continuous splicing and heating about 200 times
Fiber diameter	Cladding Diameter: 80-150µm Coating Diameter: 100-1000µm	Power supply	Input AC100-240V 50 $/$ 60HZ, output DC13.5V $/$ 4A, the current power mode can be identified, real-time detection of battery power
Fiber Cleave Length	Coating less than 250µm: 8-16mm Coating less than 250-1000µm:16mm	Operating Conditions	Temperature -15 $^{\circ}$ +50 °C, humidity: <95% RH (no condensation) Working altitude: 0 $\sim$ 5000m. Resist max. wind speed: $\leq$ 15m / s
Software updates Length	Automatically update, Update by a key	Shrinkable tube	60mm、50mm、40mm、25mm
Boot time	1 second	Product protection	Waterproof, dust proof, shock-resistant

# SIZE DETAILS





### **ACCESSORIES IN THE BOX**





Fiber Cleaver



Spare electrode



Wire stripping pliers




Miller stripper



Hex key



carrying case



Fiber for ARC calibration



Strap



Power Adapter



Alcohol Bottle



Brush



User's manual Quality Certificate Warranty Card

# REGIONT

#### SERVICE COMMITMENT



If there is quality problem from the date of purchase within three months,

we offer free replacement machine.

The customer bear the out and home shipping cost.

2

Lifetime warranty, lifetime free parts, but these circumstances are not within the scope of this provision.

- •Except for the cleaver, Miller clamp, stripping pliers, fiber holders and other tools whose life depends on the frequency of use and the use of the environment.
- Electrodes are consumables, it is termination after the electrodes splicing 3,000 times.
- Battery warranty for one year, it is in free warranty where it is damaged or can not be charged in one year.



When the splicing reaches 50,000 times,

our company will replace a brand new machine for customer free of charge.



#### ABOUT US





Our Company Is A High-Tech Enterprise Which Is Specialized In Research And Development, Production And Sales Of Communications Products. The Main Products Are Automatic Intelligent Optical Fiber Fusion Splicer, Optical Time Domain Reflectometer (OTDR), Light Power Meter, Optical Cable Construction Tools Equipment, Fiber Fusion And Taper Equipment, Optical Cable Blowing Machine Etc. Our Products Are Widely Used In China Telecom, China Mobile, China Unicom, Broadcasting, Electricity, Railways, Petrochemical, Military, Coal Industry, Research Institutions And Other Fields.

Our Company Has A Modern Production Plant And Standardized Office Buildings, With A Total Area Of Nearly 6,000 Square Meters, About 200 Employees, Including 10 Senior Engineers, 12 Master's Degree Or Above, Bachelor Degree Or Above Accounted For 45%. Our Company Owns Independent Intellectual Property Rights For Signal Fire Automatic Intelligent Optical Fiber Fusion Splicer And Its Related Products. Our Products Have Been Sold To Many Countries And Regions, Including North America, South America, Europe And Southeast Asia Etc, Our Products Have Gained Highly Praise From Customers.



Your Trusted Partner



# THANK YOU