

P | Cabling

Data sheet

OpDAT PF patch panel VIK
24xE2000 APC (green), OS2, gray

Page 1/5

P/N


1502005924-E

EAN 4251394600499


2021/08/30

Version: E

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel for fixed installation
- equipped with E2000 adapters
- light construction with aluminum front plate (gray or black) and housing
- unequipped cutouts are closed with blind plugs
- removable front plate for easy adapter mounting
- 10 possible cable entries in the rear panel for 4x PG13.5, 2x PG16/M20 or 2x PG21/M25 cable glands and for two pre-terminated installation cables (VIK)
- snap-on cover for easy access during service work
- label windows for enclosed identification labels
- variants: equipped with 12 or 24 E2000 adapters blue (OS2), lime green (OM5) or 12 or 24 E2000 APC adapters green (OS2)



P | Cabling

Data sheet

OpDAT PF patch panel VIK 24xE2000 APC (green), OS2, gray

Page 2/5

P/N
1502005924-E
EAN 4251394600499
2021/08/30
Version: E

Technical Data

General Data

Fields of application

Structured building cabling, Office
Data center

Design patch panel

Mounting style 1RU

Transmission technology Fiber optic

Port numbering yes

Color green

Dimensions

Dimension (L x W x H) 262 mm x 482.6 mm x 44.45 mm

Dimension (L x W x H) 10.315 in. x 19 in. x 1.75 in.

Inches 19 inches

Height unit 1RU

Mode type of the fiber Singlemode

Shape APC (Angled Physical Contact)

Fiber construction 9/125 µm

Labeling option label window with identification label + printed numbers

Connections/interfaces

Connector technology interface 1 E2000-S Couplers

Connector technology interface 2 E2000-S Couplers

Number of ports interface 1 24

Number of ports interface 2 24

Number of equipped ports interface 1 24

Number of ports interface 2 equipped 24

Number of ports with dust protection interface 1 24

Number of ports with dust protection interface 2 24

Cable access/outlet several possibilities for cable entry on the back

Mechanical data

Cut-out SC, LC-D, E2000

Connector type simplex

Life - Number of mating cycles min. 1000

strain relief yes



P | Cabling

Data sheet

OpDAT PF patch panel VIK 24xE2000 APC (green), OS2, gray

Page 3/5

P/N

1502005924-E

EAN 4251394600499

2021/08/30

Version: E

Technical Data

Materials and material properties

Material - Housing	Al (Aluminium)
Material - Front cover	Al (Aluminium)
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics
RoHS	compliant

Classifications

ETIM 7.0	EC001130
ETIM 8.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
Packaging dimension	540 mm x 380 mm x 60 mm
Packaging dimension	21.26 in. x 14.961 in. x 2.362 in.



P | Cabling

Data sheet

Page 4/5

OpDAT PF patch panel VIK 24xE2000 APC (green), OS2, gray

P/N

1502005924-E

EAN 4251394600499

2021/08/30

Version: E

Accessories

P/N	Designation
130792	Mounting kit, cage nuts M6
1502500000-E	OpDAT PF/fix patch cord tray gray
15081106-E	OpDAT mounting plate VIK
150811M20-E	Cable gland M20 (Clamping range 7 to 12 mm)
150811M25-E	Cable gland M25
899011-01	Label sheet for Modul patch panels / REG



P | Cabling

Data sheet

OpDAT PF patch panel VIK

24xE2000 APC (green), OS2, gray

Page 5/5

P/N

1502005924-E

EAN 4251394600499

2021/08/30

Version: E

Illustrations

Dimensional drawing

