

P | Cabling

Data sheet

OpDAT PF patch panel splice
12xE2000 (blue), OS2, gray

Page 1/6

P/N

1502095812-E

EAN 4251394600529


2021/09/01

Version: H

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19 inch 1RU fiber optic patch panel for fixed installation
- equipped with E2000 adapters and E2000 pigtails
- label windows for enclosed identification labels
- pigtails with semi-tight buffered fiber dia. 0.9 mm, 12 colors, secondary and primary coating in the same color, length 2.0 m
- pigtails inserted and stripped in standard splice tray with crimp splice holders
- pigtails are cleaned and inserted into adapters
- light construction with aluminum front plate (gray or black) and housing
- unequipped cutouts are closed with blind plugs
- snap-on cover for easy access during service work
- 10 possible cable entries in the rear panel for 4x PG13.5, 2x PG16/M20 or 2x PG21/M25 cable glands and for two pre-terminated installation cables (VIK)
- variants: equipped with 12 or 24 E2000 adapters and pigtails blue (OS2) or 12 or 24 E2000 adapters and pigtails green (OS2)



P | Cabling

Data sheet

Page 2/6

OpDAT PF patch panel splice 12xE2000 (blue), OS2, gray

P/N

1502095812-E

EAN 4251394600529

2021/09/01

Version: H

Technical Data

General Data

Fields of application

Structured building cabling, Office
Data center

Design patch panel

Mounting style 1RU

Transmission technology Fiber optic

Port numbering yes

Color blue

Dimensions

Dimension (L x W x H) 262 mm x 482.6 mm x 44.45 mm

Dimension (L x W x H) 10.315 in. x 19 in. x 1.75 in.

Inches 19 inches

Height unit 1RU

Installation depth 240 mm

Installation depth 9.449 in.

Number of cables/ buffered fibers 12

Cable Type pigtail(s)

Fiber class OS2: IEC 60793-2-50 B6_a, B6_b & ITU-T G.657.A, G.652.D

Mode type of the fiber Singlemode

Shape UPC (Ultra Physical Contact)

Fiber construction 9/125 µm

Labeling option label window with identification label + printed numbers

Connections/interfaces

Connector technology interface 1 E2000-S Couplers

Connector technology interface 2 E2000-S Couplers

Number of ports interface 1 24

Number of ports interface 2 24

Number of equipped ports interface 1 12

Number of ports interface 2 equipped 12

Number of ports with dust protection interface 2 12

Number of blind 12

Semi-tight buffered fiber pigtail length 2 m



P | Cabling

Data sheet

OpDAT PF patch panel splice 12xE2000 (blue), OS2, gray

Page 3/6

P/N

1502095812-E

EAN 4251394600529

2021/09/01

Version: H

Technical Data

Connections/interfaces

Semi-tight buffered fiber pigtail length	6.56 ft
Semi-tight buffered fiber pigtail diameter	0.9 mm
Semi-tight buffered fiber pigtail diameter	0.035 in.
Cable access/outlet	several possibilities for cable entry on the back

Optical characteristics

Insertion loss	max. 0,3 dB
Return loss	min. 65 dB

Mechanical data

Cut-out	SC, LC-D, E2000
Connector type	simplex
Life - Number of mating cycles	min. 1000
strain relief	yes

Materials and material properties

Material - Housing	Al (Aluminium)
Material - Front cover	Al (Aluminium)
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics
RoHS	compliant

The product meets the following standards

Fibre optic connector interfaces	IEC 61754-15
Optical fibers: Indoor optical cables	
Sectional specification for class B single-mode fibres	ISO/IEC 60793-2-50 type B6_a/B6_b
Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
Fibre optic interconnecting devices and passive components	IEC 61300-3-4
Fibre optic interconnecting devices and passive components	IEC 61300-3-6
Fibre optic interconnecting devices and passive components	IEC 61300-3-35
Standard colours for insulation for low-frequency cables & wires	IEC 60304



P | Cabling

Data sheet

Page 4/6

OpDAT PF patch panel splice 12xE2000 (blue), OS2, gray

P/N

1502095812-E

EAN 4251394600529

2021/09/01

Version: H

Technical Data

The product meets the following standards

ITU-T standard	ITU-T G.657.A compatible with ITU-T G.652.D
----------------	---

Classifications

ETIM 7.0	EC001130
----------	----------

ETIM 8.0	EC001130
----------	----------

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------

Packaging dimension	540 mm x 380 mm x 60 mm
---------------------	-------------------------

Packaging dimension	21.26 in. x 14.961 in. x 2.362 in.
---------------------	------------------------------------



P | Cabling

Data sheet

Page 5/6

OpDAT PF patch panel splice 12xE2000 (blue), OS2, gray

P/N

1502095812-E

EAN 4251394600529

2021/09/01

Version: H

Accessories

P/N	Designation
130792	Mounting kit, cage nuts M6
1502500000-E	OpDAT PF/fix patch cord tray gray
150811M20-E	Cable gland M20 (Clamping range 7 to 12 mm)
150811M25-E	Cable gland M25
15090301-I	OpDAT splice protection cover for 12 crimp splices
15090401-E	OpDAT crimp splice protection (12 pcs)
899011-01	Label sheet for Modul patch panels / REG



P | Cabling

Data sheet

OpDAT PF patch panel splice
12xE2000 (blue), OS2, gray

Page 6/6

P/N

1502095812-E

EAN 4251394600529

2021/09/01

Version: H

Illustrations

Dimensional drawing

