


HKI 41-34 H.264 | IPTV Encoder



- ✓ H.264 coding
- ✓ 4 × HDMI in 4 × SPTS
- ✓ Web-based configuration, remote maintenance (SMARTPortal)
- ✓ Two redundant power supplies (hot pluggable)

Order information

Type	HKI 41-34
Order no.	HKI04134
GTIN	7611682005868
PE	1
VE	1
EU customs tariff number	85432000



Technical data

Inputs

Connector	4 × HDMI
Video resolution	1080p@60 Hz
Max. bit rate per channel	16 Mbit/s
Audio Encoder	AAC, AAC+, AAC++, MP3
Video Encoder	H.264

IPTV output

Supported protocols	UDP, HTTP, RTSP, RTMP, ONVIF
Interfaces	
IPTV output	4×RJ-45, IEEE 802.3, 10/100/1000 Base-T
Configuration interface	1 × RJ-45
Compliance configuration interface	IEEE 802.3, 10/100 Base-T
Supported configuration protocols	HTTP, AXING SMARTPortal*

General

Operating voltage	2 × 100...240 VAC/50...60 Hz
Power consumption	25 W
Redundant power supply	2 × Hot pluggable
Operating temperature range (acc. to EN 60065)	0°C...+45°C
Dimensions (W × H × D) appr.	482 × 267 × 47 mm
Weight	4.100 kg
Comments	* encrypted, cloud-based application for configuration, monitoring and remote maintenance

Example of use

