

ORX 15-00 Optical receiver | Quattro



- ✓ For the reception of optical signals
- ✓ Converts optical signals into SAT IF (with fixed satellite polarisation planes) and CATV signals
- ✓ To connect to a multiswitch
- ✓ Power supply via multiswitch

Order information

Type	ORX 15-00
Order no.	ORX01500
GTIN	7611682006926
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Input	
Optical connector	SC/APC
Optical level	-14 ... -8 dBm
Wavelength	1310 nm
Optical return loss	> 45 dB
Output	
Type	TERR VL VH HL HH
Level @ 21 dB optical attenuation	82 dBμV @ DVB-C/T/T2 88 dBμV @ DVB-S/S2/S2X
Frequency range	87 ... 862 MHz @ DVB-C/T/T2 950 ... 2150 MHz @ DVB-S/S2/S2X
RF connectors	
Type	F female
Return loss	10 dB
General	
Operating voltage	14 ... 18 VDC
Power consumption	3.3 W
Current consumption	330 mA @ 18 VDC 380 mA @ 14 VDC
Operating temperature range	-5 ... +50°C
Dimensions (W × H × D) appr.	125 × 100 × 30 mm
Weight	0.324 kg

Example of use

