

SPU 996-09 Kaskadenbaustein | 9 in 6 | premium-line



- ✓ For up to 6 subscribers
- ✓ Passive satellite and terrestrial path
- ✓ For cascadable 9 in x SAT systems
- ✓ Optimized for the use with SPU 9xx-09
- ✓ Suitable for return path

Order information

Type	SPU 996-09
Order no.	SPU99609
GTIN	7611682139952
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Inputs	
Number	9
Frequency range	5...65 MHz 85...862 MHz 950...2200 MHz
Subscriber ports	
Number	6
Tap loss TERR	20 dB
Tap loss SAT	19...16 dB
Isolation	>26 dB
Switching isolation	>26 dB
Trunk outputs	
Number	9
Through loss TERR	5 dB
Through loss SAT	2...5 dB
Isolation	>30 dB
Rejection (SAT TERR)	>40 dB
Connectors	
Connector type	F
General	
Operating temperature range (acc. to EN 60065)	-20...+50°C
Dimensions (W × H × D) appr.	230 × 125 × 40 mm
Weight	0.606 kg

[illegible]

QEW 3-12 Earthing angle | single-rowed | quickfix
CFA 11-00 Terminating resistor | 75 Ohm | DC isolated
CFA 4-01 Adapter F/F | Quickfix