

SPU 998-09 Kaskadenbaustein | 9 in 8 | premium-line



- ✓ For up to 8 subscribers
- ✓ Passive satellite and terrestrial path
- ✓ For cascadable 9 in x SAT systems
- ✓ Optimized for the use with SPU 9xx-09
- ✓ Suitable for return path

Order information


Type	SPU 998-09
Order no.	SPU99809
GTIN	7611682139969
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Inputs	
Number	9
Frequency range	5...65 MHz 85...862 MHz 950...2200 MHz
Subscriber ports	
Number	8
Tap loss TERR	22 dB
Tap loss SAT	19...16 dB
Isolation	>26 dB
Switching isolation	>26 dB
Trunk outputs	
Number	9
Through loss TERR	5 dB
Through loss SAT	2...5 dB
Isolation	>30 dB
Rejection (SAT TERR)	>40 dB
Connectors	
Connector type	F
General	
Operating temperature range (acc. to EN 60065)	-20...+50°C
Dimensions (W × H × D) appr.	230 × 145 × 40 mm
Weight	0.700 kg

Example of use



Suitable products

QEW 4-12 Earthing angle | single-rowed | quickfix

CFA 11-00 Terminating resistor | 75 Ohm | DC isolated

CFA 4-01 Adapter F/F | Quickfix