


SSD 5-07 SAT end outlet terminated 7 dB | 5...2200 MHz | CATV | SAT



- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Suitable for return path 5...65 MHz
- ✓ Suitable for Unicable I (EN50494) and Unicable II (EN50607)
- ✓ Easy to install
- ✓ Stripping length 8/13 mm
- ✓ Extended F socket
- ✓ Surface treaded
- ✓ Vodafone Kabel Deutschland approved

Order information

Type	SSD 5-07
Order no.	SSD00507
GTIN	7611682001662
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Screening factor acc. to EN 50083-2	Class A (+ 10 dB)
Tap method	Filter circuit/directional coupler
Trunk line	
Frequency range input	5...2200 MHz
Suitable cables (Inner conductor outer diameter)	0.63...1.13 mm 4.70...7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	109...862 MHz / 5...65 MHz
Tap loss	7 dB $\pm$ 1.5 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5...125 MHz
Tap loss	9 dB $\pm$ 2.0 dB
SAT connector	
Connector type	F female
Frequency range	950...2200 MHz
Tap loss	7 dB $\pm$ 1.5 dB
DC power pass to trunk	yes
General	
Dimensions (W x H x D) appr.	68 x 68 x 39 mm
Weight	0.104 kg

Suitable products

[SZU 2-00 Cover plate | TV/R/SAT | single piece](#)

[TZU 1-00 Surface frame](#)

[SZU 2-10 Cover plate | TV/R/SAT | two-parts](#)

[TZU 1-10 Surface frame](#)