

Dämpfungsregler

Adjustable attenuator



Artikel Article	TZU 4-00	TZU 4-01
Artikelnummer Part No.	TZU00400	TZU00401
Verpackungseinheit Packing unit	1	
CE ■ KLASSE CLASS A   Advanced Network Design		
Schirmungsmaß Screening factor	> 75 dB	
Frequenzbereich Frequency range	0,1...1006 MHz	
Dämpfung, einstellbar Attenuator adjustment range	0,5...20 dB	
Anschlüsse Connectors	IEC-Buchse/IEC-Stecker IEC-female/IEC-male	F-Buchse/F-Stecker F-female/F-male

Kabelentzerrer, einstellbar

Adjustable equalizer



Artikel Article	TZU 7-00	TZU 8-00	TZU 9-00
Artikelnummer Part No.	TZU00700	TZU00800	TZU00900
Verpackungseinheit Packing unit	1		
CE KLASSE A ULTRA HD AND Advanced Network Design			
Frequenzbereich Frequency range	5...446 MHz	5...606 MHz	5...862 MHz
Durchgangsdämpfung Through loss		≤ 1,5 dB	
Rückflusssdämpfung Return loss	≥ 15 dB	≥ 15 dB	≥ 12 dB
Entzerrung Slope		0...18 dB	
Anschlüsse Connectors		F-Buchse/F-Stecker F-female/F-male	