

Data sheet

Page 1/4

Consolidation Point VIK 6xE2000-D APC OS2 (ceramic, green)

P/N

1503005F06-E


EAN 4251394603506

2018-26-02

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- Consolidation Point VIK with E2000-D adapters
- To connect pre-terminated installation cables VIK with max. 12 fibers
- Wall-mount powder-coated steel-sheet housing, (white, RAL 9010)
- Patch area with swing-open and removable cover with label field
- Possibility for strain relief for patch cord
- Not used cutouts are closed by blind plugs
- Cable management area with separate cover
- Possible cable entry on the back side for one PG16 cable gland
- If necessary order extensions or reductions for the fixing of the VIKs as separate accessory
- Supplied with material for wall-mounting
- Variants: equipped with 6 E2000-D adapters blue (OS2) or green (OS2 APC)



Data sheet

Page 2/4

Consolidation Point VIK 6xE2000-D APC OS2 (ceramic, green)

P/N

1503005F06-E

EAN 4251394603506

2018-26-02

Technical Data

General Data

Fields of application	Structured building cabling, Office
Transmission technology	Fiber optic
Color	green
Dimensions	
Dimension (L x W x H)	128.20 x 29.60 x 339.00 mm
Dimension (L x W x H)	5.047 x 1.165 x 13.346 in.
Fiber class	OS2: IEC 60793-2-50 B6_a, B6_b & ITU-T G.657.A, G.652.D
Mode type of the fiber	Single mode
Shape	APC (Angled Physical Contact)
Fiber construction	9/125 µm
Labeling option	label window with identification label + printed numbers

Connections/interfaces

Connector technology interface 1	E2000-D Couplers
Connector technology interface 2	E2000-D Couplers
Number of ports interface 1	6
Number of ports interface 2	6
Number of equipped ports interface 1	6
Number of ports interface 2 equipped	6
Number of ports with dust protection interface 1	6
Number of ports with dust protection interface 2	6
Cable access/outlet	possibility for cable entry on the back

Mechanical characteristics

Connector type	Duplex
Life - Number of mating cycles	min. 1000
strain relief	yes

Materials and material properties

Material - Housing	sheet steel
Material - Housing finish	powder-coated
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics



Data sheet

Page 3/4

Consolidation Point VIK 6xE2000-D APC OS2 (ceramic, green)

P/N

1503005F06-E

EAN 4251394603506

2018-26-02

Technical Data

Approvals

RoHS compliant

The product meets the following standards

Fibre optic connector interfaces DIN EN 61754-15

Packing details

Type of packaging	1 pc(s) / box
Packaging dimension (W x H x D)	470.00 x 200.00 x 60.00 mm
Packaging dimension (W x H x D)	18.504 x 7.874 x 2.362 in.



Illustrations

Dimensional drawing

