

PSU-300M/288 AND PSU-300/432 CENTRAL OFFICE CABINET



Central Office Cabinet PSU-300/432

FEATURES:

- dedicated for installation in telecommunication central offices with limited space and high number of cables and connectors
- provides 432 fibre terminations in compact housing
- accepts 36 MPK-12 modules
- minimises initial installation expenditures thanks to the modular construction with MPK-12 modules
- high capacity, ease of installation and efficient fibre management
- top and/or bottom outdoor cable or multipatchcord brush entries
- key locked door
- stable and rigid construction
- special zone to reserve accumulation of patchcord

THE SET INCLUDES:

- housing, key locked front door
- outdoor cable fixing and fibre distribution plate
- indoor cable fixing plate
- installation and handling instructions
- installation kit

ADDITIONAL EQUIPMENT:

- MPK-12 modules
- fibre manifold R-01A - for 144 fibre count outdoor cable (option)
- fibre manifold R-01E - for 48 fibre count outdoor cable (option)

TECHNICAL SPECIFICATIONS:

	PSU-300M/288	PSU-300/432
number of lateral cable management sections	1	
number of splice trays	24 x KSQ	36 x KSQ
maximum number of splices	288	432
module type	MPK-12	
number of modules	24	36
connector standard	E-2000, SC	
adapter capacity	288	432
maximum diameter of input cable [mm]	22	
dimensions: width/height/depth [mm]	300/2200/300	
recommended pigtail length [m], 0.9 mm buffered fibre	1,5	
weight [kg]	40	41
housing material/colour	steel sheet/RAL 7035	

ORDERING:

PSU-300/432 - central office cabinet with 432 fibre termination capacity, width 300 mm, depth 300 mm