


TRX Minicables for Use in Microducts

Cable Design



- not to scale -

- **Buffer:** All fibres are grouped together in an easy strippable natural coating.
- **Strength member:** aramid yarns.
- **Outer sheath:** high e-modulus thermoplastic compound.

This dielectric optical cable is designed for outdoor installation in microducts by blowing or pulling techniques.

Technical data

No. of Fibres		4		
Cable Diameter	mm	1.8 ± 0.2		
Cable Weight	kg / km	3		
Min. bending radius	mm	Without Tension 15 x Cable-Ø		Under Maximum Tension 25 x Cable-Ø
Temperature range	°C	Installation -10 to +50	Transport. & Storage -30 to +70	Operation -20 to +60

Main characteristics

Test	Standard	Specified value	Acceptance Criteria ⁽²⁾
Tensile Performance	IEC 60794-1-2-E1	150 N	$\Delta\alpha \leq 0.05$ dB
Crush	IEC 60794-1-2-E3	500N, 100mm, 1 min	$\Delta\alpha \leq 0.05$ dB during test, no damage
Impact	IEC 60794-1-2-E3	3 Nm, R=300mm, 3 impacts	no damage
Repeated bending	IEC 60794-1-2-E6	R=25xD, 100 cycles	$\Delta\alpha \leq 0.05$ dB
Torsion	IEC 60794-1-2-E7	±180°, L=1m, 10 cycles	$\Delta\alpha \leq 0.05$ dB
Kink	IEC 60794-1-2-E10	min diameter=30mm	no damage
Cable bend	IEC 60794-1-2-E11	R=25xD, 5 turns, 3 cycles	$\Delta\alpha \leq 0.05$ dB
Temperature range ⁽¹⁾	IEC 60794-1-2-F1	-20 to +60°C -30 to +70°C	$\Delta\alpha \leq 0.05$ dB $\Delta\alpha$ reversible

⁽¹⁾ temperature cycling test shall be performed on cable coil (without drum)


⁽²⁾ values for single mode fibres, all optical measurements performed at 1550 nm.

Optical Characteristics

See attached cabled optical fibre data sheet.

Identification

Fibre Colours

No.	1	2	3	4	5	6	7	8	9	10	11	12
Colour	red	blue	white	green	yellow	grey	brown	black	violet	orange	aqua	pink
												

Sheath Colour:

The outer sheath colour is green.

Sheath Marking:

The outer sheath is marked in 1 meter intervals as follows:

PRYSMIAN(SR) <year/week of manufacture> SUPREME <no. and type of fibres>
IDno. <cable ID> <length marking>m

Logistic

Packing:

Plywood drums with protection

Delivery Lengths:

Standard delivery lengths are 2km and 4km with a tolerance of -1% / +3%

© PrysmianGroup 2018, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by PrysmianGroup.