


Evolv™ Terminal with Pushlok™ Technology 8 port, stubbed, SST Dielectric, 250 m

CORNING

Part Number:
DMA8F1FDD1NC250M0P

Pushlok™ hardened connector technology is the key component enabling smaller terminals for FTTx networks than ever before. Designed for use in nearly every access network environment, the terminal is small enough to be placed in existing handholes or pedestals where space is paramount, on building facades, or in aerial networks (pole- or strand-mount). Improved aesthetics improve end-user adoption for facade applications. There are two styles of terminals designed to meet various space and density requirements: terminals with one row of adapter ports and terminals with two rows of adapter ports. For terminals with one row of adapter ports, the ports are aligned in a single row with the input stub on the left and 2-, 4-, 6- or 8-distribution ports on the right. For terminals with two rows of ports, the input stub is on the front left of the terminal and there are 6-, 8-, 12- or 16- distribution ports. Each port's corresponding release button is actuated to remove the dust cap or drop. When installing drops, the keyed ports provide an audible and physical positive feedback minimizing technician variation and potential damage due to mishandling.



Evolv™ Terminal with Pushlok™ Technology, 8 port, stubbed, SST Dielectric, 250 m

Features and Benefits

Pushlok™ cable assembly connector ports for customer drop terminations

Lower installation cost and increased speed of connection

Standard and integrated splitter terminal options **Durability**

Solution supports various architecture types

Durability

100 lb cable tensile strength

Available stubbed or preterminated with OptiTip® multifiber connector technology

Compatible with existing FlexNAP™ installations

Small form factor optimizes space in pedestals/ handholes

Lower profile overall with drop entry ports on bottom

Ultrasonically welded housing

Eliminates water ingress potential and prevents unwanted entry in the field

Factory-terminated polished connectors

Eliminates loss associated with excess fusion splices

Available stubbed or preterminated with OptiTip® multifiber connector technology

Compatible with existing FlexNAP™ installations

Available stubbed or preterminated with OptiTip®

Evolv™ Terminal with Pushlok™ Technology 8 port, stubbed, SST Dielectric, 250 m

CORNING

Specifications

General Specifications

Product Type	Terminals
Environment	Outdoor
Cable Type	SST Flat Dielectric Drop
Fiber Category	ITU-TG.652.D (OS2)
Packaging	Individual Pack
Preconnectorized "Stubbed" Hardware	No
Lockable	No
Cable type stubbed	SST Drop Cable
Mounting Type	Strand mount, Pole-mount, Wall-Mountable, Pedestal mount, Handhole Mount
Splice option	No
Application	FTTx

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature Range, Operation	-40 °C to 85 °C
Temperature Range, Storage	-40 °C to 85 °C

Design

Fiber Count	8
Input Fiber Count	8
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black
Fibers per Port	1
Number of single-fiber ports, SC APC connector	8

Evolv™ Terminal with Pushlok™ Technology 8 port, stubbed, SST Dielectric, 250 m

CORNING

Design

Housing Material	Plastic
Pigtail Length	250 m
Polish	APC
Input Cable Type	SST Flat Dielectric Drop
Locking Availability	No
Sealing Type	Welded
Housing Color	Black
Pigtail Type	Dielectric
Number of Ports	8

Design - Adapter

Adapter Type	Pushlok
--------------	---------

Mechanical Specifications

Cable Length	250 m
Cold Mate/Demate	-40 °C

Optical Specification - Hardware

Module Insertion Loss, Max	0.5 dB
Reflectance, Maximum	65 dB

Connector Specs

Connector Type	Pushlok
Housing Color	Black
Housing Material	Plastic
Polish	APC

Evolv™ Terminal with Pushlok™ Technology 8 port, stubbed, SST Dielectric, 250 m

CORNING

Specifications - Connector A

Connector Type	Pushlok
Housing Color	Black
Polish	APC
Housing Material	Plastic
Endface Type	APC
Insertion Loss, Max.	0.5 dB
Reflectance	> 65 dB
Insertion Loss, Typical	≤ 0.15 dB

Dimensions

Length	154 mm
Height	30 mm
Width	134 mm

Shipping Dimensions

Height	846 mm
Width	846 mm
Depth	178 mm

Ordering Information

Product Number	DMA8F1FDD1NC250M0P
Weight	9.35 kg
Packaging Method	Reel
Shipping Weight	9 kg
Width	846 mm
Depth	178 mm
Height	846 mm

**Evolv™ Terminal with Pushlok™ Technology 8
port, stubbed, SST Dielectric, 250 m**



Ordering Information	
Units per Delivery	1/1



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.