



- data sheet -

Cable blowing machine

Blue Dragon Jet Max

With a supplementary small blowing head



**** Warranty 3 years!!! ****

Technical data	BDJ MAX with a supplementary small blowing head
Cable's diameter	6.0 – 15mm /20mm available as an option
Duct's diameter	32 mm, 40mm, 50mm
Supplementary STANDARD blowing head	Ø cable: $4.0 - 10$ mm $/ 2.5 + 12$ mm available as an option Ø ducts:: $5.0 - 16$ mm $/ 20$ mm available as an option
Blowing distance / max	2500 m
Blowing speed / max	110 m/min
Work pressure / max	10 bar
Dimensions of the unit /L x W x H/	620 x 300 x 380mm /weight approx. 35kg
Dimensions of the transport trunk	690 x 430 x 440mm /weigh approx. 48kg
Required compressor's efficiency	micro ducts up till 8mm -0,8m3/min micro ducts 8-12mm -1,0m3/min micro ducts 12-16mm - 1,5m3/min micro ducts 15-20mm - 3,5m3/min ducts 32-40-50 mm - 8 - 10 m3/min
	BDJ MAX products set includes handles for every diameter of HDPE ducts, all necessary seals for cables and ducts, tools calibrating plates, a socket wrench, an air hose for a 10 bar compressor, and a robust transport trunk. Supplementary (small) Standard blowing head includes: a set of bushings and seals for micro ducts (5-16mm), as well as the seals and bushings for each cable size (in the range of 2.5mm-12mm) and a 10m air hose for the compressor, socked wrench
	Free of charge: micro duct calibration bullets (5,7,8 mm), micro duct cutter, Prelube5000 liquid-240 ml, pneumatic oil