



FC/UPC-FC/UPC SM Simplex 3.0mm
(With Standard Boot)



FC/UPC-FC/UPC SM Simplex 3.0mm
(With Rubber Boot)



ST/UPC-ST/UPC SM Duplex 3.0mm



LC/UPC-LC/UPC SM Duplex 2.0mm
(With White Boot)



LC/UPC-LC/UPC OM3 Duplex 3.0mm
(With Red/Black Boot)



LC/UPC-LC/UPC OM3 Duplex 2.0mm
(All Aqua Connector Kits)



MU/UPC-MU/UPC SM Simplex 2.0mm



MTRJ/F-MTRJ/F MM Duplex 1.8mm
(With Flat Boot)



LC/UPC-E2000/APC SM Duplex 2.0mm

■ Default Cable Jacket Color

Fiber Type	Jacket Color
OS2 Singlemode 9/125μm	Yellow
OM1 Multimode 62.5/125μm	Orange
OM2 Multimode 50/125μm	Orange
OM3 Multimode 50/125μm	Aqua
OM4 Multimode 50/125μm	Aqua or Violet

■ Fire Retardant fiber optic cables

Abbreviation	Fire Retardant Rate
OFNR	Optical Fiber, Nonconductive, Riser
OFNP	Optical Fiber, Nonconductive, Plenum
LSZH	Low Smoke Zero Halogen

*Special jacket color available upon request, please contact with your sales representative for more details.

Patch Cords	1st Termination	2nd Termination	Fiber Type
Standard JS	SC/UPC SU MT-RJ/Female JF	SC/UPC SU MT-RJ/Female JF	OS2 9
	SC/APC SA MT-RJ/Male JM	SC/APC SA MT-RJ/Male JM	OM1 62.5/125 1
	FC/UPC FU E2000/PC EP	FC/UPC FU E2000/PC EP	OM2 50/125 2
	FC/APC FA E2000/APC EA	FC/APC FA E2000/APC EA	OM3 50/125 3
	ST/UPC TU DIN/PC DP	ST/UPC TU DIN/PC DP	OM4 50/125 4
	LC/UPC LU DIN/APC DA	LC/UPC LU DIN/APC DA	G.657.A1 7
	LC/APC LA D4/PC D4	LC/APC LA D4/PC D4	G.657.A2 A
	MU/UPC MU	MU/UPC MU	

Cable Configuration	Cable O.D.	Cable Jacket	Cable Color	Overall Length	*Customized
Simplex S	250μm 0	No Jacket N	Yellow Y	1M 010	Reference R
Duplex Zipcord D	900μm Tight Buffer 1	PVC(Riser) P	Orange O	1.5M 015	
Duplex Round R	900μm Semi-tight Buffer S	Plenum M	Blue L	...	
Duplex Flat F	900μm Loose Tube L	LSZH L	White W		
	2.0mm 2		Aqua A		
	3.0mm 3		Pink P		
	1.6mm A		Violet V		
	1.8mm B		...		
	2.4mm C				
	...				

Ordering Example: JS-SASA9S3-LY020



*Fiberyo uses the standard TIA/EIA-598 color coded fiber. This color code is used for quick and easy identification of individual fibers.