


## NGO-12 WALL-MOUNTED FIBRE OPTIC OUTLET



Wall-Mounted Fibre Optic Outlet  
NGO-12



Wall-Mounted Fibre Optic Outlet  
NGO-12

### FEATURES:

- network termination in customer's apartment
- installed directly on the wall or on flush-mounting box  $\varnothing 60$  mm
- maximum capacity: 2 SC connectors or 4 LC connectors, 2 splice protectors
- access to adapters protected by automatically closing shutters

### EQUIPMENT:

- installation and handling instruction
- installation kit
- optionally with an adapter and pigtail

### TECHNICAL SPECIFICATIONS:

|  | NGO-12                  |
|--|-------------------------|
| maximum number of splices                              | 4                       |
| number of patching fields                              | 2 x E-2000/SC/LC Duplex |
| total pigtail spare length (0.9 mm buffered fibre) [m] | 4                       |
| total cable spare length (2mm) [mm]                    | 1                       |
| dimensions: width/height/depth [mm]                    | 86/86/25                |
| weight [kg]  | 0,08                    |
| housing material                                       | ABS V0                  |
| colour   | RAL 9016                |
| mechanical IK protection                               | IK08                    |
| environmental IP protection                            | IP54                    |

### ORDERING:

NGO-12-1SCA- Wall-Mounted Fibre Optic Outlet, equipped with 1 pigtail and SC/APC adapter

